3BDH000601R1 1/3



PRODUCT-DETAILS

# **3BDH000601R1**SA920B Power Supply



**General Information** 

3BDH000601R1 2/3

3BDH000601R1 Product ID **ABB Type Designation** SA920B **Catalog Description** SA920B Power Supply The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for mashalling and wiring are reduced. The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units. S900 I/O type B. For installation in hazardous area Zone 2. For connecting intrinsically safe field devices installed in Zone 2, Zone 1 or Zone 0. SA920B Power Supply for 24V DC, for redundant termination unit TU921B (TU16R-B) in Long Description S900 I/O. Do not mix SA910B with SA920B for redundancy (observe Release Notes). - ATEX Certification for installation in Zone 2 - Redundancy (Power and Communication) - Hot Configuration in Run - Hot Swap functionality - Extended Diagnostic - Excellent configuration and diagnostics via FDT/DTM - G3-coating for all components - Simplified maintenance with auto-diagnostics - Powering of communication interfaces and I/O modules - How swap capability in Zone 2

### **Additional Information**

Medium Description
For 24 V DC. The power supply filter type BP901S is not required. SA920B is the functional replacement for SA910B. Do not mix SA910B with SA920B for redundancy (observe Release Notes)

Product Type
Power\_Supply

## Ordering

HS Code

850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS
THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE
AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND
ACCESSORIES OF SUCH ARTICLES; Electrical transformers, static
converters (for example, rectifiers) and inductors; Static converters

Customs Tariff Number

85044083

Dimensions	
Product Net Depth / Length	117 mm
Product Net Height	129 mm
Product Net Width	47 mm
Product Net Weight	1.6 kg

### **Environmental**

RoHS Status Following EU Directive 2011/65/EU

- Redundant powering

- Alarm in case of power failure (with redundancy)
- Switching On by tighten the 4 switch-on interlock screws

3BDH000601R1 3/3

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries	0
SCIP	d91afac0-c5db-4483-b73c-0014e2eb0387 Germany

# **Categories**

Control System Products  $\rightarrow$  I/O Products  $\rightarrow$  S900 I/O  $\rightarrow$  S900 I/O - Power Supplies  $\rightarrow$  SA920B Power Supply Control Systems  $\rightarrow$  800xA  $\rightarrow$  I/Os  $\rightarrow$  S900 I/O  $\rightarrow$  Power Supplies Control Systems  $\rightarrow$  800xA  $\rightarrow$  I/Os  $\rightarrow$  S900 I/O  $\rightarrow$  Power Supplies

