3KDE175363L9100 1/3



PRODUCT-DETAILS

3KDE175363L9100DP910N Frequency Input (FI2)



General Information

3KDE175363L9100 2/3

Product ID3KDE175363L9100ABB Type DesignationDP910NCatalog DescriptionDP910N Frequency Input (FI2)

The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for mashalling and wiring are reduced.

The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units.

S900 I/O type N. For installation in safe (= non-hazardous) area.

DP910N Frequency Input (FI2), input for dry contacts or proximity switches.

Long Description

- Redundancy (Power and Communication)

- Hot Configuration in Run

- Hot Swap functionality

- Extended Diagnostic

- Excellent configuration and diagnostics via FDT/DTM

- G3-coating for all components

- Simplified maintenance with auto-diagnostics

- Frequency input for dry contacts or proximity switches

- Short and break detection

- Eletrical isolation between input / bus and input / power

- Frequency measurement or counting applications

- 2 Function blocks

- Reset via fieldbus or control input

- Status outputs / Direction recognition

Additional Information

Medium Description	Input for dry contact or NAMUR initiator.
Product Type	I-O_Module

Ordering

Channels

HS Code

853890 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS
THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE
AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND
ACCESSORIES OF SUCH ARTICLES;Parts suitable for use solely or
principally with the apparatus of heading|8535, 8536|or 8537;Other

Customs Tariff Number

85389099

Dimensions	
Product Net Depth / Length	104 mm
Product Net Height	20 mm
Product Net Width	104 mm
Product Net Weight	0.125 kg

Technical Channel Type Number of Input

DΙ

2

3KDE175363L9100 3/3

Environmental	
RoHS Status	Following EU Directive 2011/65/EU
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries	0
SCIP	424b7e5e-adce-406e-b168-4925b1a2efac Germany

Categories

 $Control \ System \ Products \rightarrow I/O \ Products \rightarrow S900 \ I/O \rightarrow S900 \ I/O - Modules \rightarrow DP910N \ Frequency \ Input$

Control Systems ightarrow 800xA ightarrow I/Os ightarrow S900 I/O ightarrow I/O Modules

Control Systems \rightarrow 800xA \rightarrow I/Os \rightarrow S900 I/O \rightarrow I/O Modules

