




---

 PRODUCT-DETAILS

## ACS580-01-206A-4+B056

LV AC general purpose wall-mounted drive,  
IEC: Pn 110 kW, 206 A, 400 V (ACS580-01-206A-4+B056)




---

**General Information**


---

<b>Global Commercial Alias:</b>	ACS580-01-206A-4+B056
<b>Product ID:</b>	3AUA0000083581
<b>ABB Type Designation:</b>	ACS580-01-206A-4+B056
<b>EAN:</b>	6438177306122
<b>Catalog Description:</b>	LV AC general purpose wall-mounted drive, IEC: Pn 110 kW, 206 A, 400 V (ACS580-01-206A-4+B056)
<b>Long Description:</b>	The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture. All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.
<b>Display Name:</b>	ACS580-01-206A-4+B056

## Ordering

<b>Customs Tariff Number:</b>	850440
<b>HS Code:</b>	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
<b>Invoice Description:</b>	ACS580-01-206A-4+B056 PN: 110 kW, IN: 206 A
<b>Made To Order:</b>	Yes
<b>Minimum Order Quantity:</b>	1 piece
<b>Order Multiple:</b>	1 piece
<b>Quote Only:</b>	No
<b>Selling Unit of Measure:</b>	piece

## Dimensions

<b>Product Net Weight:</b>	56 kg 123.459 lb
<b>Product Net Depth / Length:</b>	381.00 mm 15.000 in
<b>Product Net Height:</b>	880.00 mm 34.646 in
<b>Product Net Width:</b>	284.00 mm 11.181 in
<b>Package Level 1 Depth / Length:</b>	992.00 mm 39.055 in
<b>Package Level 1 Height:</b>	568.00 mm 22.362 in
<b>Package Level 1 Width:</b>	400.00 mm 15.748 in
<b>Package Level 1 Units:</b>	case 1 piece

## Technical

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	722 W	91.5 %	0.5 %
0/50 %	1001 W	93.7 %	0.7 %
0/100 %	1797 W	94.2 %	1.3 %
50/25 %	793 W	95.3 %	0.6 %
50/50 %	1138 W	96.5 %	0.8 %
50/100 %	2116 W	96.7 %	1.5 %
90/50 %	1345 W	97.6 %	0.9 %
90/100 %	2785 W	97.5 %	2.0 %

<b>Number of Phases:</b>	3-phase
<b>Degree of Protection:</b>	IP55
<b>Enclosure Type NEMA:</b>	Type12
<b>Altitude:</b>	1000 m
<b>Operating Humidity (RH<sub>amb</sub>):</b>	95
<b>Sound dB (A):</b>	67 dB(A)
<b>Multiple Battery Information:</b>	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
<b>Frequency (f):</b>	47.5 ... 63 Hz
<b>Frame Size:</b>	R7
<b>Input Voltage (U<sub>in</sub>):</b>	380 ... 480 V
<b>Mounting Type:</b>	Wall-mounted
<b>Communication Protocol:</b>	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
<b>Number of Hardware Interfaces:</b>	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
<b>Includes:</b>	Control unit PC connection
<b>Analog Inputs:</b>	2
<b>Analog Outputs:</b>	2
<b>Number of Digital In/Outputs:</b>	6 / 3
<b>Output Current, Normal Use (I<sub>n</sub>):</b>	206 A
<b>Output Current, Light-Overload Use (I<sub>LD</sub>):</b>	196 A
<b>Output Current, Heavy-Duty Use (I<sub>HD</sub>):</b>	169 A
<b>Output Power, Normal Use (P<sub>n</sub>):</b>	110 kW
<b>Output Power, Light-Overload Use (P<sub>LD</sub>):</b>	110 kW
<b>Output Power, Heavy-Duty Use (P<sub>HD</sub>):</b>	90 kW
<b>Power Consumption (@P<sub>cons</sub>):</b>	2785 W
<b>Apparent Power Output:</b>	143 kV·A
<b>Efficiency Level:</b>	IE2
<b>Standby Loss:</b>	36 W
<b>Temperature Rating:</b>	Maximum 50 °C Minimum -15 °C

---

## Certificates and Declarations

---

<b>Declaration of Conformity - CE:</b>	3AXD10001818627
<b>REACH Date:</b>	20250905
<b>REACH Declaration:</b>	9AKK107992A7060
<b>REACH Information:</b>	True - contains substances > 0.1 mass percentage
<b>RoHS Date:</b>	20240508
<b>RoHS Declaration:</b>	3AXD10001818627
<b>RoHS Information:</b>	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

---



---

## Environmental

---

<b>SCIP:</b>	93c4256e-49ac-4f3a-a0ee-89382f71d90e Finland
<b>WEEE Category:</b>	4. Large Equipment (Any External Dimension More Than 50 cm)

---



---

## External Classifications and Standards

---

<b>ETIM 9:</b>	EC001857 - Frequency converter =< 1 kV
<b>ETIM 10:</b>	EC001857 - Frequency converter =< 1 kV
<b>UNSPSC:</b>	39122001

---



---

## Categories

---

Products > Drives > Low Voltage AC Drives > General Purpose Drives > ACS580-01 - Wall-mounted drive

