



 PRODUCT-DETAILS

ACS580-04-880A-4

LV AC general purpose drive module, IEC: Pn 500 kW, 880 A, 400 V, UL: Pld 700 Hp, 807 A, 480 V (ACS580-04-880A-4)



General Information

Global Commercial Alias:	ACS580-04-880A-4
Product ID:	3AUA0000170525
ABB Type Designation:	ACS580-04-880A-4
EAN:	6438177340478
Catalog Description:	LV AC general purpose drive module, IEC: Pn 500 kW, 880 A, 400 V, UL: Pld 700 Hp, 807 A, 480 V (ACS580-04-880A-4)
Long Description:	<p>The ACS580-04 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.</p> <p>All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The ACS580-04 drive module comes in IP00 enclosure as standard for cabinet installation. Also, IP20 enclosure is available.</p>
Display Name:	ACS580-04-880A-4

Ordering

Customs Tariff Number:	85044087
HS Code:	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
Invoice Description:	ACS580-04-880A-4 PN: 500 kW, IN: 880 A
Made To Order:	Yes
Minimum Order Quantity:	1 piece
Order Multiple:	1 piece
Quote Only:	No
Selling Unit of Measure:	piece

Dimensions

Product Net Weight:	199 kg 438.720 lb
Product Net Depth / Length:	529 mm 20.827 in
Product Net Height:	1662 mm 65.433 in
Product Net Width:	350 mm 13.780 in
Package Level 1 Depth / Length:	2050 mm 80.71 in
Package Level 1 Height:	500 mm 19.69 in
Package Level 1 Width:	650 mm 25.59 in
Package Level 1 Units:	1 case

Technical

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	2916 W	93.0 %	0.4 %
0/50 %	4164 W	94.8 %	0.6 %
0/100 %	7551 W	95.3 %	1.0 %
50/25 %	3134 W	96.3 %	0.4 %
50/50 %	4641 W	97.2 %	0.6 %
50/100 %	8766 W	97.3 %	1.2 %
90/50 %	5366 W	98.2 %	0.7 %
90/100 %	10887 W	98.1 %	1.5 %

Number of Phases:	3-phase
Degree of Protection:	IP00
Enclosure Type NEMA:	Open Type
Altitude:	1000 m
Operating Humidity (RH_{amb}):	95
Sound dB (A):	71 dB(A)
Multiple Battery Information:	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f):	47.5 ... 63 Hz
Frame Size:	R11
Input Voltage (U_{in}):	380 ... 480 V
Mounting Type:	Module
Communication Protocol:	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces:	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes:	Control unit PC connection
Analog Inputs:	2
Analog Outputs:	2
Number of Digital In/Outputs:	6 / 3
Output Current, Normal Use (I_n):	880 A
Output Current, Light-Overload Use (I_{LD}):	865 A
Output Current, Heavy-Duty Use (I_{HD}):	725 A
Output Power, Normal Use (P_n):	500 kW
Output Power, Light-Overload Use (P_{LD}):	500 kW
Output Power, Heavy-Duty Use (P_{HD}):	400 kW
Power Consumption (@P_{cons}):	10887 W
Apparent Power Output:	610 kV·A
Efficiency Level:	IE2
Standby Loss:	615 W
Temperature Rating:	Maximum 40 °C Minimum -15 °C

Technical UL

Output Current, Heavy-Duty Use (UL):	625 A
Output Current, Light-Overload Use (UL):	807 A
Output Current, Normal Use (UL):	880 A
Output Power, Heavy-Duty Use (UL):	500 Hp
Output Power, Light-Overload Use (UL):	700 Hp

Certificates and Declarations

Declaration of Conformity - CE:	3AXD10001818627
REACH Date:	20250905
REACH Declaration:	9AKK107992A7060
REACH Information:	True - contains substances > 0.1 mass percentage
RoHS Date:	20240508
RoHS Declaration:	3AXD10001818627
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

SCIP:	e9fd22a6-81c4-4079-87c1-83e8cf566d7a Finland
WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9:	EC001857 - Frequency converter =< 1 kV
ETIM 10:	EC001857 - Frequency converter =< 1 kV
UNSPSC:	39122001

Categories

Products > Drives > Low Voltage AC Drives > General Purpose Drives > ACS580-04 - Drive module

