



 PRODUCT-DETAILS

ACS580-07-0169A-4

LV AC general purpose cabinet-built drive,
IEC: Pn 90 kW, 169 A, 400 V, UL: Pld 125 Hp,
156 A, 480 V (ACS580-07-0169A-4)



General Information

Global Commercial Alias:	ACS580-07-0169A-4
Product ID:	3AXD50000041422
ABB Type Designation:	ACS580-07-0169A-4
Catalog Description:	LV AC general purpose cabinet-built drive, IEC: Pn 90 kW, 169 A, 400 V, UL: Pld 125 Hp, 156 A, 480 V (ACS580-07-0169A-4)
Long Description:	<p>The ACS580-07 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.</p> <p>All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The ready-made standalone cabinet-built ACS580-07 variant comes in IP21 as standard. Also, IP42 and IP54 units are available.</p>
Display Name:	ACS580-07-0169A-4

Ordering

Customs Tariff Number:	85044087
HS Code:	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES; Electrical transformers, static converters (for example, rectifiers) and inductors; Static converters
Invoice Description:	ACS580-07-0169A-4 PN: 90 kW, IN: 169 A
Made To Order:	Yes
Minimum Order Quantity:	1 piece
Order Multiple:	1 piece
Quote Only:	No
Selling Unit of Measure:	piece

Dimensions

Product Net Weight:	220 kg 485.017 lb
Product Net Depth / Length:	673 mm 26.496 in
Product Net Height:	2145 mm 84.449 in
Product Net Width:	430 mm 16.929 in
Package Level 1 Depth / Length:	2520 mm 99.213 in
Package Level 1 Height:	900 mm 35.433 in
Package Level 1 Width:	820 mm 32.283 in
Package Level 1 Units:	1 case

Technical

Number of Phases:	3-phase
Degree of Protection:	IP21
Enclosure Type NEMA:	Type1
Operating Humidity (RH_{amb}):	5 to 95%
Sound dB (A):	67 dB(A)
Multiple Battery Information:	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f):	47.5 ... 63 Hz
Frame Size:	R7
Input Voltage (U_{in}):	380 ... 480 V
Mounting Type:	Cabinet-built

Communication Protocol:	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces:	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes:	Control unit PC connection
Analog Inputs:	2
Analog Outputs:	2
Number of Digital In/Outputs:	6 / 3
Output Current, Normal Use (I_n):	169 A
Output Current, Light-Overload Use (I_{LD}):	161 A
Output Current, Heavy-Duty Use (I_{HD}):	145 A
Output Power, Normal Use (P_n):	90 kW
Output Power, Light-Overload Use (P_{LD}):	90 kW
Output Power, Heavy-Duty Use (P_{HD}):	75 kW
Power Consumption (@P_{cons}):	2497 W
Apparent Power Output:	117 kV-A
Temperature Rating:	Maximum 40 °C Minimum 0 °C
Ecodesign Exemption:	Energy efficiency data is not provided for this cabinet-based drive. Cabinet built drives, with already conform modules, are excluded from the scope of the EU ecodesign requirements (Regulation EU/2019/1781, §2.3.e).

Technical UL

Output Current, Heavy-Duty Use (UL):	124 A
Output Current, Light-Overload Use (UL):	156 A
Output Power, Heavy-Duty Use (UL):	100 Hp
Output Power, Light-Overload Use (UL):	125 Hp

Certificates and Declarations

Declaration of Conformity - CE:	3AXD10001818627
REACH Date:	20250905

REACH Declaration:	9AKK107992A7060
REACH Information:	True - contains substances > 0.1 mass percentage
RoHS Date:	20240508
RoHS Declaration:	3AXD10001818627
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

SCIP:	f8697513-3243-4f24-9777-7dbe1d791662 Finland
WEEE Category:	4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9:	EC001857 - Frequency converter =< 1 kV
ETIM 10:	EC001857 - Frequency converter =< 1 kV
UNSPSC:	39122001

Categories

Products > Drives > Low Voltage AC Drives > General Purpose Drives > ACS580-07 - Cabinet-built drive

