



PRODUCT-DETAILS

ACS560-01-089A-4

ACS560-01-089A-4



General Information

Global Commercial Alias:	ACS560-01-089A-4
Product ID:	3AXD50001276898
ABB Type Designation:	ACS560-01-089A-4
Catalog Description:	ACS560-01-089A-4
Display Name:	ACS560-01-089A-4

Ordering

Customs Tariff Number:	85044040
HS Code:	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters
Invoice Description:	ACS560-01-089A-4
Made To Order:	Yes
Minimum Order Quantity:	1 piece
Order Multiple:	1 piece
Quote Only:	No

Selling Unit of Measure:	piece
--------------------------	-------

Dimensions

Product Net Depth / Length:	257 mm
Product Net Height:	636 mm
Product Net Width:	203 mm

Technical

Number of Phases:	3-phase
Degree of Protection:	IP20
Multiple Battery Information:	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Mounting Type:	Wall-mounted
Communication Protocol:	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces:	Industrial Ethernet 0 Other 2 Parallel 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes:	Control unit PC connection
Analog Inputs:	2
Analog Outputs:	2
Output Current, Normal Use (I_n):	89 A
Output Current, Light-Overload Use (I_{LD}):	83 A
Output Current, Heavy-Duty Use (I_{HD}):	89 A
Output Power, Normal Use (P_n):	45 kW
Output Power, Light-Overload Use (P_{LD}):	45 kW
Output Power, Heavy-Duty Use (P_{HD}):	45 kW
Apparent Power Output:	62 kV·A

Categories

Products > Drives > Low Voltage AC Drives > General Purpose Drives > ACS560-01 - Wall-mounted drive

