



Figure similar

SIPLUS S7-1500 CPU 1513-1 PN based on 6ES7513-1AM03-0AB0 with conformal coating -40...+70 °C . central processing unit with work memory 600 KB for program and 2.5 MB for data, 1st interface: PROFINET IRT with 2-port switch, 25 ns bit performance, SIMATIC Memory Card required

| General information                                      |                                                                                                   |
|----------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Product type designation                                 | CPU 1513-1 PN                                                                                     |
| Firmware version                                         |                                                                                                   |
| • FW update possible                                     | Yes                                                                                               |
| based on                                                 | <a href="#">6ES7513-1AM03-0AB0</a>                                                                |
| Product function                                         |                                                                                                   |
| • I&M data                                               | Yes; I&M0 to I&M3                                                                                 |
| • Isochronous mode                                       | Yes; Distributed and central; with minimum OB 6x cycle of 500 µs (distributed) and 1 ms (central) |
| • SysLog                                                 | Yes                                                                                               |
| Engineering with                                         |                                                                                                   |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275                                                                           |
| Configuration control                                    |                                                                                                   |
| via dataset                                              | Yes                                                                                               |
| Display                                                  |                                                                                                   |
| Screen diagonal [cm]                                     | 3.45 cm                                                                                           |
| Control elements                                         |                                                                                                   |
| Number of keys                                           | 8                                                                                                 |
| Mode buttons                                             | 2                                                                                                 |
| Supply voltage                                           |                                                                                                   |
| Rated value (DC)                                         | 24 V                                                                                              |
| permissible range, lower limit (DC)                      | 19.2 V                                                                                            |
| permissible range, upper limit (DC)                      | 28.8 V                                                                                            |
| Reverse polarity protection                              | Yes                                                                                               |
| Mains buffering                                          |                                                                                                   |
| • Mains/voltage failure stored energy time               | 5 ms                                                                                              |
| • Repeat rate, min.                                      | 1/s                                                                                               |
| Input current                                            |                                                                                                   |
| Current consumption (rated value)                        | 0.56 A                                                                                            |
| Current consumption, max.                                | 0.9 A                                                                                             |
| Inrush current, max.                                     | 1.15 A; Rated value                                                                               |
| I <sup>2</sup> t                                         | 0.6 A <sup>2</sup> ·s                                                                             |
| Power                                                    |                                                                                                   |
| Infeed power to the backplane bus                        | 10 W                                                                                              |
| Power consumption from the backplane bus (balanced)      | 5.5 W                                                                                             |
| Power loss                                               |                                                                                                   |
| Power loss, typ.                                         | 3.4 W                                                                                             |
| Memory                                                   |                                                                                                   |
| Number of slots for SIMATIC memory card                  | 1                                                                                                 |

|                                                           |                                                                                                                                                       |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| SIMATIC memory card required                              | Yes                                                                                                                                                   |
| <b>Work memory</b>                                        |                                                                                                                                                       |
| • integrated (for program)                                | 600 kbyte                                                                                                                                             |
| • integrated (for data)                                   | 2.5 Mbyte                                                                                                                                             |
| <b>Load memory</b>                                        |                                                                                                                                                       |
| • Plug-in (SIMATIC Memory Card), max.                     | 32 Gbyte                                                                                                                                              |
| <b>Backup</b>                                             |                                                                                                                                                       |
| • maintenance-free                                        | Yes                                                                                                                                                   |
| <b>CPU processing times</b>                               |                                                                                                                                                       |
| for bit operations, typ.                                  | 25 ns                                                                                                                                                 |
| for word operations, typ.                                 | 32 ns                                                                                                                                                 |
| for fixed point arithmetic, typ.                          | 42 ns                                                                                                                                                 |
| for floating point arithmetic, typ.                       | 170 ns                                                                                                                                                |
| <b>CPU-blocks</b>                                         |                                                                                                                                                       |
| Number of elements (total)                                | 4 000; Blocks (OB, FB, FC, DB) and UDTs                                                                                                               |
| <b>DB</b>                                                 |                                                                                                                                                       |
| • Number range                                            | 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999 |
| • Size, max.                                              | 2.5 Mbyte; For DBs with absolute addressing, the max. size is 64 KB                                                                                   |
| <b>FB</b>                                                 |                                                                                                                                                       |
| • Number range                                            | 0 ... 65 535                                                                                                                                          |
| • Size, max.                                              | 600 kbyte                                                                                                                                             |
| <b>FC</b>                                                 |                                                                                                                                                       |
| • Number range                                            | 0 ... 65 535                                                                                                                                          |
| • Size, max.                                              | 600 kbyte                                                                                                                                             |
| <b>OB</b>                                                 |                                                                                                                                                       |
| • Size, max.                                              | 600 kbyte                                                                                                                                             |
| • Number of free cycle OBs                                | 100                                                                                                                                                   |
| • Number of time alarm OBs                                | 20                                                                                                                                                    |
| • Number of delay alarm OBs                               | 20                                                                                                                                                    |
| • Number of cyclic interrupt OBs                          | 20; With minimum OB 3x cycle of 250 µs                                                                                                                |
| • Number of process alarm OBs                             | 50                                                                                                                                                    |
| • Number of DPV1 alarm OBs                                | 3                                                                                                                                                     |
| • Number of isochronous mode OBs                          | 2                                                                                                                                                     |
| • Number of technology synchronous alarm OBs              | 2                                                                                                                                                     |
| • Number of startup OBs                                   | 100                                                                                                                                                   |
| • Number of asynchronous error OBs                        | 4                                                                                                                                                     |
| • Number of synchronous error OBs                         | 2                                                                                                                                                     |
| • Number of diagnostic alarm OBs                          | 1                                                                                                                                                     |
| <b>Nesting depth</b>                                      |                                                                                                                                                       |
| • per priority class                                      | 24                                                                                                                                                    |
| <b>Counters, timers and their retentivity</b>             |                                                                                                                                                       |
| <b>S7 counter</b>                                         |                                                                                                                                                       |
| • Number                                                  | 2 048                                                                                                                                                 |
| <b>Retentivity</b>                                        |                                                                                                                                                       |
| — adjustable                                              | Yes                                                                                                                                                   |
| <b>IEC counter</b>                                        |                                                                                                                                                       |
| • Number                                                  | Any (only limited by the main memory)                                                                                                                 |
| <b>Retentivity</b>                                        |                                                                                                                                                       |
| — adjustable                                              | Yes                                                                                                                                                   |
| <b>S7 times</b>                                           |                                                                                                                                                       |
| • Number                                                  | 2 048                                                                                                                                                 |
| <b>Retentivity</b>                                        |                                                                                                                                                       |
| — adjustable                                              | Yes                                                                                                                                                   |
| <b>IEC timer</b>                                          |                                                                                                                                                       |
| • Number                                                  | Any (only limited by the main memory)                                                                                                                 |
| <b>Retentivity</b>                                        |                                                                                                                                                       |
| — adjustable                                              | Yes                                                                                                                                                   |
| <b>Data areas and their retentivity</b>                   |                                                                                                                                                       |
| Retentive data area (incl. timers, counters, flags), max. | 256 kbyte; in total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 216 KB                           |

|                                                                    |                                                                                                                                                                                                                                   |
|--------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended retentive data area (incl. timers, counters, flags), max. | 2.5 Mbyte; When using PS 6 0W 24/48/60 V DC HF                                                                                                                                                                                    |
| <b>Flag</b>                                                        |                                                                                                                                                                                                                                   |
| • Size, max.                                                       | 16 kbyte                                                                                                                                                                                                                          |
| • Number of clock memories                                         | 8; 8 clock memory bit, grouped into one clock memory byte                                                                                                                                                                         |
| <b>Data blocks</b>                                                 |                                                                                                                                                                                                                                   |
| • Retentivity adjustable                                           | Yes                                                                                                                                                                                                                               |
| • Retentivity preset                                               | No                                                                                                                                                                                                                                |
| <b>Local data</b>                                                  |                                                                                                                                                                                                                                   |
| • per priority class, max.                                         | 64 kbyte; max. 16 KB per block                                                                                                                                                                                                    |
| <b>Address area</b>                                                |                                                                                                                                                                                                                                   |
| Number of IO modules                                               | 2 048; max. number of modules / submodules                                                                                                                                                                                        |
| <b>I/O address area</b>                                            |                                                                                                                                                                                                                                   |
| • Inputs                                                           | 32 kbyte; All inputs are in the process image                                                                                                                                                                                     |
| • Outputs                                                          | 32 kbyte; All outputs are in the process image                                                                                                                                                                                    |
| per integrated IO subsystem                                        |                                                                                                                                                                                                                                   |
| — Inputs (volume)                                                  | 8 kbyte                                                                                                                                                                                                                           |
| — Outputs (volume)                                                 | 8 kbyte                                                                                                                                                                                                                           |
| per CM/CP                                                          |                                                                                                                                                                                                                                   |
| — Inputs (volume)                                                  | 8 kbyte                                                                                                                                                                                                                           |
| — Outputs (volume)                                                 | 8 kbyte                                                                                                                                                                                                                           |
| <b>Subprocess images</b>                                           |                                                                                                                                                                                                                                   |
| • Number of subprocess images, max.                                | 32                                                                                                                                                                                                                                |
| <b>Hardware configuration</b>                                      |                                                                                                                                                                                                                                   |
| Number of distributed IO systems                                   | 32; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| <b>Number of DP masters</b>                                        |                                                                                                                                                                                                                                   |
| • Via CM                                                           | 6; A maximum of 6 CMs (PROFINET + PROFIBUS) can be inserted in total                                                                                                                                                              |
| <b>Number of IO Controllers</b>                                    |                                                                                                                                                                                                                                   |
| • integrated                                                       | 1                                                                                                                                                                                                                                 |
| • Via CM                                                           | 6; A maximum of 6 CMs (PROFINET + PROFIBUS) can be inserted in total                                                                                                                                                              |
| <b>Rack</b>                                                        |                                                                                                                                                                                                                                   |
| • Modules per rack, max.                                           | 32; CPU + 31 modules                                                                                                                                                                                                              |
| • Number of lines, max.                                            | 1                                                                                                                                                                                                                                 |
| <b>PtP CM</b>                                                      |                                                                                                                                                                                                                                   |
| • Number of PtP CMs                                                | the number of connectable PtP CMs is only limited by the number of available slots                                                                                                                                                |
| <b>Time of day</b>                                                 |                                                                                                                                                                                                                                   |
| <b>Clock</b>                                                       |                                                                                                                                                                                                                                   |
| • Type                                                             | Hardware clock                                                                                                                                                                                                                    |
| • Backup time                                                      | 6 wk; At 40 °C ambient temperature, typically                                                                                                                                                                                     |
| • Deviation per day, max.                                          | 10 s; Typ.: 2 s                                                                                                                                                                                                                   |
| <b>Operating hours counter</b>                                     |                                                                                                                                                                                                                                   |
| • Number                                                           | 16                                                                                                                                                                                                                                |
| <b>Clock synchronization</b>                                       |                                                                                                                                                                                                                                   |
| • supported                                                        | Yes                                                                                                                                                                                                                               |
| • to DP, master                                                    | Yes; via PROFIBUS CM / CP                                                                                                                                                                                                         |
| • on DP, device                                                    | Yes; via PROFIBUS CM / CP                                                                                                                                                                                                         |
| • in AS, master                                                    | Yes                                                                                                                                                                                                                               |
| • in AS, device                                                    | Yes                                                                                                                                                                                                                               |
| • on Ethernet via NTP                                              | Yes                                                                                                                                                                                                                               |
| <b>Interfaces</b>                                                  |                                                                                                                                                                                                                                   |
| Number of PROFINET interfaces                                      | 1                                                                                                                                                                                                                                 |
| <b>1. Interface</b>                                                |                                                                                                                                                                                                                                   |
| <b>Interface types</b>                                             |                                                                                                                                                                                                                                   |
| • RJ 45 (Ethernet)                                                 | Yes; X1                                                                                                                                                                                                                           |
| • Number of ports                                                  | 2                                                                                                                                                                                                                                 |
| • integrated switch                                                | Yes                                                                                                                                                                                                                               |
| <b>Protocols</b>                                                   |                                                                                                                                                                                                                                   |
| • IP protocol                                                      | Yes; IPv4                                                                                                                                                                                                                         |
| • PROFINET IO Controller                                           | Yes                                                                                                                                                                                                                               |

|                                                                                                                                                                                            |                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• PROFINET IO Device</li> <li>• SIMATIC communication</li> <li>• Open IE communication</li> <li>• Web server</li> <li>• Media redundancy</li> </ul> | <p>Yes</p> <p>Yes</p> <p>Yes; Optionally also encrypted</p> <p>Yes</p> <p>Yes</p>                                                                                      |
| <b>PROFINET IO Controller</b>                                                                                                                                                              |                                                                                                                                                                        |
| <b>Services</b>                                                                                                                                                                            |                                                                                                                                                                        |
| — Isochronous mode                                                                                                                                                                         | Yes                                                                                                                                                                    |
| — Direct data exchange                                                                                                                                                                     | Yes; Requirement: IRT and isochronous mode (MRPD optional)                                                                                                             |
| — IRT                                                                                                                                                                                      | Yes                                                                                                                                                                    |
| — PROFINergy                                                                                                                                                                               | Yes; per user program                                                                                                                                                  |
| — Prioritized startup                                                                                                                                                                      | Yes; Max. 32 PROFINET devices                                                                                                                                          |
| — Number of connectable IO Devices, max.                                                                                                                                                   | 128; In total, up to 512 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET                                                                       |
| — Of which IO devices with IRT, max.                                                                                                                                                       | 64                                                                                                                                                                     |
| — Number of connectable IO Devices for RT, max.                                                                                                                                            | 128                                                                                                                                                                    |
| — of which in line, max.                                                                                                                                                                   | 128                                                                                                                                                                    |
| — Number of IO Devices that can be simultaneously activated/deactivated, max.                                                                                                              | 8; in total across all interfaces                                                                                                                                      |
| — Number of IO Devices per tool, max.                                                                                                                                                      | 8                                                                                                                                                                      |
| — Updating times                                                                                                                                                                           | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| — PROFINET Security Class                                                                                                                                                                  | 1                                                                                                                                                                      |
| <b>Update time for IRT</b>                                                                                                                                                                 |                                                                                                                                                                        |
| — for send cycle of 250 µs                                                                                                                                                                 | 250 µs to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 500 µs of the isochronous OB is decisive                                    |
| — for send cycle of 500 µs                                                                                                                                                                 | 500 µs to 8 ms                                                                                                                                                         |
| — for send cycle of 1 ms                                                                                                                                                                   | 1 ms to 16 ms                                                                                                                                                          |
| — for send cycle of 2 ms                                                                                                                                                                   | 2 ms to 32 ms                                                                                                                                                          |
| — for send cycle of 4 ms                                                                                                                                                                   | 4 ms to 64 ms                                                                                                                                                          |
| — With IRT and parameterization of "odd" send cycles                                                                                                                                       | Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3 875 µs)                                                                               |
| <b>Update time for RT</b>                                                                                                                                                                  |                                                                                                                                                                        |
| — for send cycle of 250 µs                                                                                                                                                                 | 250 µs to 128 ms                                                                                                                                                       |
| — for send cycle of 500 µs                                                                                                                                                                 | 500 µs to 256 ms                                                                                                                                                       |
| — for send cycle of 1 ms                                                                                                                                                                   | 1 ms to 512 ms                                                                                                                                                         |
| — for send cycle of 2 ms                                                                                                                                                                   | 2 ms to 512 ms                                                                                                                                                         |
| — for send cycle of 4 ms                                                                                                                                                                   | 4 ms to 512 ms                                                                                                                                                         |
| <b>PROFINET IO Device</b>                                                                                                                                                                  |                                                                                                                                                                        |
| <b>Services</b>                                                                                                                                                                            |                                                                                                                                                                        |
| — Isochronous mode                                                                                                                                                                         | No                                                                                                                                                                     |
| — IRT                                                                                                                                                                                      | Yes                                                                                                                                                                    |
| — PROFINergy                                                                                                                                                                               | Yes; per user program                                                                                                                                                  |
| — Shared device                                                                                                                                                                            | Yes                                                                                                                                                                    |
| — Number of IO Controllers with shared device, max.                                                                                                                                        | 4                                                                                                                                                                      |
| — activation/deactivation of I-devices                                                                                                                                                     | Yes; per user program                                                                                                                                                  |
| — Asset management record                                                                                                                                                                  | Yes; per user program                                                                                                                                                  |
| — PROFINET Security Class                                                                                                                                                                  | SNMP Configuration and DCP Read Only                                                                                                                                   |
| <b>Interface types</b>                                                                                                                                                                     |                                                                                                                                                                        |
| <b>RJ 45 (Ethernet)</b>                                                                                                                                                                    |                                                                                                                                                                        |
| • 100 Mbps                                                                                                                                                                                 | Yes                                                                                                                                                                    |
| • Autonegotiation                                                                                                                                                                          | Yes                                                                                                                                                                    |
| • Autocrossing                                                                                                                                                                             | Yes                                                                                                                                                                    |
| • Industrial Ethernet status LED                                                                                                                                                           | Yes                                                                                                                                                                    |
| <b>Protocols</b>                                                                                                                                                                           |                                                                                                                                                                        |
| PROFIsafe                                                                                                                                                                                  | No                                                                                                                                                                     |
| <b>Number of connections</b>                                                                                                                                                               |                                                                                                                                                                        |
| • Number of connections, max.                                                                                                                                                              | 128; via integrated interfaces of the CPU and connected CPs / CMs                                                                                                      |
| • Number of connections reserved for ES/HMI/web                                                                                                                                            | 10                                                                                                                                                                     |
| • Number of connections via integrated interfaces                                                                                                                                          | 88                                                                                                                                                                     |
| • Number of S7 routing paths                                                                                                                                                               | 16                                                                                                                                                                     |

|                                                                                                        |                                                                                    |
|--------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Redundancy mode                                                                                        |                                                                                    |
| • H-Sync forwarding                                                                                    | Yes                                                                                |
| Media redundancy                                                                                       |                                                                                    |
| — Media redundancy                                                                                     | only via 1st interface (X1)                                                        |
| — MRP                                                                                                  | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0, MRP Manager; MRP Client |
| — MRP interconnection, supported                                                                       | Yes; as MRP ring node according to IEC 62439-2 Edition 3.0                         |
| — MRPD                                                                                                 | Yes; Requirement: IRT                                                              |
| — Switchover time on line break, typ.                                                                  | 200 ms; For MRP, bumpless for MRPD                                                 |
| — Number of stations in the ring, max.                                                                 | 50                                                                                 |
| SIMATIC communication                                                                                  |                                                                                    |
| • PG/OP communication                                                                                  | Yes; encryption with TLS V1.3 pre-selected                                         |
| • S7 routing                                                                                           | Yes                                                                                |
| • Data record routing                                                                                  | Yes                                                                                |
| • S7 communication, as server                                                                          | Yes                                                                                |
| • S7 communication, as client                                                                          | Yes                                                                                |
| • User data per job, max.                                                                              | See online help (S7 communication, user data size)                                 |
| Open IE communication                                                                                  |                                                                                    |
| • TCP/IP                                                                                               | Yes                                                                                |
| — Data length, max.                                                                                    | 64 kbyte                                                                           |
| — several passive connections per port, supported                                                      | Yes                                                                                |
| • ISO-on-TCP (RFC1006)                                                                                 | Yes                                                                                |
| — Data length, max.                                                                                    | 64 kbyte                                                                           |
| • UDP                                                                                                  | Yes                                                                                |
| — Data length, max.                                                                                    | 2 kbyte; 1 472 bytes for UDP broadcast                                             |
| — UDP multicast                                                                                        | Yes; max. 78 multicast circuits                                                    |
| • DHCP                                                                                                 | Yes                                                                                |
| • DNS                                                                                                  | Yes                                                                                |
| • SNMP                                                                                                 | Yes                                                                                |
| • DCP                                                                                                  | Yes                                                                                |
| • LLDP                                                                                                 | Yes                                                                                |
| • Encryption                                                                                           | Yes; Optional                                                                      |
| Web server                                                                                             |                                                                                    |
| • HTTP                                                                                                 | Yes; Standard and user pages                                                       |
| • HTTPS                                                                                                | Yes; Standard and user pages                                                       |
| • web API                                                                                              |                                                                                    |
| — Number of sessions, max.                                                                             | 50                                                                                 |
| — number of simultaneous HTTP calls, max.                                                              | 4                                                                                  |
| — HTTP request body, max.                                                                              | 131 072 byte                                                                       |
| OPC UA                                                                                                 |                                                                                    |
| • Runtime license required                                                                             | Yes; "Small" license required                                                      |
| • OPC UA Client                                                                                        | Yes; Data Access (registered Read/Write), Method Call                              |
| — Application authentication                                                                           | Yes                                                                                |
| — Security policies                                                                                    | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256    |
| — User authentication                                                                                  | "anonymous" or by user name & password                                             |
| — Number of connections, max.                                                                          | 4                                                                                  |
| — Number of nodes of the client interfaces, recommended max.                                           | 1 000                                                                              |
| — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList, max.   | 300                                                                                |
| — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max.                                | 20                                                                                 |
| — Number of elements for one call of OPC-UA_MethodGetHandleList, max.                                  | 100                                                                                |
| — Number of simultaneous calls of the client instructions for session management, per connection, max. | 1                                                                                  |
| — Number of simultaneous calls of the client instructions for data access, per connection, max.        | 5                                                                                  |
| — Number of registerable nodes, max.                                                                   | 5 000                                                                              |
| — Number of registerable method calls of OPC-UA_MethodCall, max.                                       | 100                                                                                |

|                                                                 |                                                                                                                          |
|-----------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max. | 20                                                                                                                       |
| • OPC UA Server                                                 | Yes; Data Access (Read, Write, Subscribe), Method Call, Alarms & Condition (A&C), Custom Address Space                   |
| — Application authentication                                    | Yes                                                                                                                      |
| — Security policies                                             | available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256, Aes128Sha256RsaOaep, Aes256Sha256RsaPss |
| — User authentication                                           | "anonymous" or by user name & password                                                                                   |
| — GDS support (certificate management)                          | Yes                                                                                                                      |
| — Number of sessions, max.                                      | 32                                                                                                                       |
| — Number of accessible variables, max.                          | 50 000                                                                                                                   |
| — Number of registerable nodes, max.                            | 10 000                                                                                                                   |
| — Number of subscriptions per session, max.                     | 50                                                                                                                       |
| — Sampling interval, min.                                       | 100 ms                                                                                                                   |
| — Publishing interval, min.                                     | 200 ms                                                                                                                   |
| — Number of server methods, max.                                | 20                                                                                                                       |
| — Number of inputs/outputs per server method, max.              | 20                                                                                                                       |
| — Number of monitored items, recommended max.                   | 4 000; for 1 s sampling interval and 1 s send interval                                                                   |
| — Number of server interfaces, max.                             | 10 of each "Server interfaces" / "Companion specification" type and 20 of the type "Reference namespace"                 |
| — Number of nodes for user-defined server interfaces, max.      | 15 000                                                                                                                   |
| • Alarms and Conditions                                         | Yes                                                                                                                      |
| — Number of program alarms                                      | 100                                                                                                                      |
| — Number of alarms for system diagnostics                       | 50                                                                                                                       |
| <b>Further protocols</b>                                        |                                                                                                                          |
| • MODBUS                                                        | Yes; MODBUS TCP                                                                                                          |
| <b>S7 message functions</b>                                     |                                                                                                                          |
| Number of login stations for message functions, max.            | 32                                                                                                                       |
| Program alarms                                                  | Yes                                                                                                                      |
| Number of configurable program messages, max.                   | 5 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH                                     |
| Number of loadable program messages in RUN, max.                | 2 500                                                                                                                    |
| Number of simultaneously active program alarms                  |                                                                                                                          |
| • Number of program alarms                                      | 600                                                                                                                      |
| • Number of alarms for system diagnostics                       | 100                                                                                                                      |
| • Number of alarms for motion technology objects                | 160                                                                                                                      |
| <b>Test commissioning functions</b>                             |                                                                                                                          |
| Joint commission (Team Engineering)                             | Yes; Parallel online access possible for up to 5 engineering systems                                                     |
| Status block                                                    | Yes; Up to 8 simultaneously (in total across all ES clients)                                                             |
| Single step                                                     | No                                                                                                                       |
| Number of breakpoints                                           | 8                                                                                                                        |
| Profiling                                                       | Yes                                                                                                                      |
| <b>Status/control</b>                                           |                                                                                                                          |
| • Status/control variable                                       | Yes                                                                                                                      |
| • Variables                                                     | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters                                                     |
| • Number of variables, max.                                     |                                                                                                                          |
| — of which status variables, max.                               | 200; per job                                                                                                             |
| — of which control variables, max.                              | 200; per job                                                                                                             |
| <b>Forcing</b>                                                  |                                                                                                                          |
| • Forcing                                                       | Yes                                                                                                                      |
| • Forcing, variables                                            | Peripheral inputs/outputs                                                                                                |
| • Number of variables, max.                                     | 200                                                                                                                      |
| <b>Diagnostic buffer</b>                                        |                                                                                                                          |
| • present                                                       | Yes                                                                                                                      |
| • Number of entries, max.                                       | 1 000                                                                                                                    |
| — of which powerfail-proof                                      | 500                                                                                                                      |
| <b>Traces</b>                                                   |                                                                                                                          |
| • Number of configurable Traces                                 | 4                                                                                                                        |
| • Memory size per trace, max.                                   | 512 kbyte                                                                                                                |
| <b>Interrupts/diagnostics/status information</b>                |                                                                                                                          |
| Diagnostics indication LED                                      |                                                                                                                          |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• RUN/STOP LED</li> <li>• ERROR LED</li> <li>• MAINT LED</li> <li>• STOP ACTIVE LED</li> <li>• Connection display LINK TX/RX</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Yes<br>Yes<br>Yes<br>Yes<br>Yes                                                                                                                                                                                                                                                        |
| <b>Supported technology objects</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                        |
| Motion Control <ul style="list-style-type: none"> <li>• Number of available Motion Control resources for technology objects</li> <li>• Required Motion Control resources               <ul style="list-style-type: none"> <li>— per speed-controlled axis</li> <li>— per positioning axis</li> <li>— per synchronous axis</li> <li>— per external encoder</li> <li>— per output cam</li> <li>— per cam track</li> <li>— per probe</li> </ul> </li> <li>• Positioning axis               <ul style="list-style-type: none"> <li>— Number of positioning axes at motion control cycle of 4 ms (typical value)</li> <li>— Number of positioning axes at motion control cycle of 8 ms (typical value)</li> </ul> </li> </ul> | Yes; Note: The number of technology objects affects the cycle time of the PLC program; selection guide via the TIA Selection Tool<br>1 120<br>40<br>80<br>160<br>80<br>20<br>160<br>40<br>11<br>14                                                                                     |
| Controller <ul style="list-style-type: none"> <li>• PID_Compact</li> <li>• PID_3Step</li> <li>• PID-Temp</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Yes; Universal PID controller with integrated optimization<br>Yes; PID controller with integrated optimization for valves<br>Yes; PID controller with integrated optimization for temperature                                                                                          |
| Counting and measuring <ul style="list-style-type: none"> <li>• High-speed counter</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Yes                                                                                                                                                                                                                                                                                    |
| <b>Standards, approvals, certificates</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                        |
| Ecological footprint <ul style="list-style-type: none"> <li>• environmental product declaration</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Yes                                                                                                                                                                                                                                                                                    |
| Global warming potential <ul style="list-style-type: none"> <li>— global warming potential, (total) [CO2 eq]</li> <li>— global warming potential, (during production) [CO2 eq]</li> <li>— global warming potential, (during operation) [CO2 eq]</li> <li>— global warming potential, (after end of life cycle) [CO2 eq]</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                       | 80.1 kg<br>23.8 kg<br>57.4 kg<br>-1.29 kg                                                                                                                                                                                                                                              |
| <b>Ambient conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                        |
| Ambient temperature during operation <ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | -40 °C; = Tmin (incl. condensation/frost)<br>70 °C; = Tmax; display: 50 °C, the display is switched off at an operating temperature of typically 50 °C<br>-40 °C; = Tmin<br>40 °C; = Tmax; display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off |
| Ambient temperature during storage/transportation <ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | -40 °C<br>70 °C                                                                                                                                                                                                                                                                        |
| Altitude during operation relating to sea level <ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual                                                                                                                                                                                                                 |
| Relative humidity <ul style="list-style-type: none"> <li>• With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation                                                                                                                                                                                      |
| <b>Resistance</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                        |
| Coolants and lubricants <ul style="list-style-type: none"> <li>— Resistant to commercially available coolants and lubricants</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Yes; Incl. diesel and oil droplets in the air                                                                                                                                                                                                                                          |
| Use in stationary industrial systems <ul style="list-style-type: none"> <li>— to biologically active substances according to EN 60721-3-3</li> <li>— to chemically active substances according to EN</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request<br>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity                                                                                                      |

|                                                                                                                         |                                                                                                                                                                                     |         |                |
|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------------|
| 60721-3-3                                                                                                               | degree 3); *                                                                                                                                                                        |         |                |
| — to mechanically active substances according to EN 60721-3-3                                                           | Yes; Class 3S4 incl. sand, dust, *                                                                                                                                                  |         |                |
| Use on ships/at sea                                                                                                     |                                                                                                                                                                                     |         |                |
| — to biologically active substances according to EN 60721-3-6                                                           | Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)                                                                                                                    |         |                |
| — to chemically active substances according to EN 60721-3-6                                                             | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *                                                                                            |         |                |
| — to mechanically active substances according to EN 60721-3-6                                                           | Yes; Class 6S3 incl. sand, dust; *                                                                                                                                                  |         |                |
| Usage in industrial process technology                                                                                  |                                                                                                                                                                                     |         |                |
| — Against chemically active substances acc. to EN 60654-4                                                               | Yes; Class 3 (excluding trichlorethylene)                                                                                                                                           |         |                |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                            | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |         |                |
| Remark                                                                                                                  |                                                                                                                                                                                     |         |                |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04             | * The supplied plug covers must remain in place over the unused interfaces during operation!                                                                                        |         |                |
| Conformal coating                                                                                                       |                                                                                                                                                                                     |         |                |
| • Coatings for printed circuit board assemblies acc. to EN 61086                                                        | Yes; Class 2 for high reliability                                                                                                                                                   |         |                |
| • Protection against fouling acc. to EN 60664-3                                                                         | Yes; Type 1 protection                                                                                                                                                              |         |                |
| • Military testing according to MIL-I-46058C, Amendment 7                                                               | Yes; Discoloration of coating possible during service life                                                                                                                          |         |                |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A                                                                                                                                                     |         |                |
| configuration / header                                                                                                  |                                                                                                                                                                                     |         |                |
| configuration / programming / header                                                                                    |                                                                                                                                                                                     |         |                |
| Programming language                                                                                                    |                                                                                                                                                                                     |         |                |
| — LAD                                                                                                                   | Yes                                                                                                                                                                                 |         |                |
| — FBD                                                                                                                   | Yes                                                                                                                                                                                 |         |                |
| — STL                                                                                                                   | Yes                                                                                                                                                                                 |         |                |
| — SCL                                                                                                                   | Yes                                                                                                                                                                                 |         |                |
| — CFC                                                                                                                   | Yes                                                                                                                                                                                 |         |                |
| — GRAPH                                                                                                                 | Yes                                                                                                                                                                                 |         |                |
| Know-how protection                                                                                                     |                                                                                                                                                                                     |         |                |
| • User program protection/password protection                                                                           | Yes                                                                                                                                                                                 |         |                |
| • Copy protection                                                                                                       | Yes                                                                                                                                                                                 |         |                |
| • Block protection                                                                                                      | Yes                                                                                                                                                                                 |         |                |
| Access protection                                                                                                       |                                                                                                                                                                                     |         |                |
| • protection of confidential configuration data                                                                         | Yes                                                                                                                                                                                 |         |                |
| • Password for display                                                                                                  | Yes                                                                                                                                                                                 |         |                |
| • Protection level: Write protection                                                                                    | Yes                                                                                                                                                                                 |         |                |
| • Protection level: Read/write protection                                                                               | Yes                                                                                                                                                                                 |         |                |
| • Protection level: Write protection for Failsafe                                                                       | No                                                                                                                                                                                  |         |                |
| • Protection level: Complete protection                                                                                 | Yes                                                                                                                                                                                 |         |                |
| • User administration                                                                                                   | Yes; device-wide                                                                                                                                                                    |         |                |
| programming / cycle time monitoring / header                                                                            |                                                                                                                                                                                     |         |                |
| • lower limit                                                                                                           | adjustable minimum cycle time                                                                                                                                                       |         |                |
| • upper limit                                                                                                           | adjustable maximum cycle time                                                                                                                                                       |         |                |
| Dimensions                                                                                                              |                                                                                                                                                                                     |         |                |
| Width                                                                                                                   | 35 mm                                                                                                                                                                               |         |                |
| Height                                                                                                                  | 147 mm                                                                                                                                                                              |         |                |
| Depth                                                                                                                   | 129 mm                                                                                                                                                                              |         |                |
| Weights                                                                                                                 |                                                                                                                                                                                     |         |                |
| Weight, approx.                                                                                                         | 400 g                                                                                                                                                                               |         |                |
| Classifications                                                                                                         |                                                                                                                                                                                     |         |                |
|                                                                                                                         |                                                                                                                                                                                     | Version | Classification |
|                                                                                                                         | eClass                                                                                                                                                                              | 14      | 27-24-22-07    |
|                                                                                                                         | eClass                                                                                                                                                                              | 12      | 27-24-22-07    |
|                                                                                                                         | eClass                                                                                                                                                                              | 9.1     | 27-24-22-07    |

|        |     |             |
|--------|-----|-------------|
| eClass | 9   | 27-24-22-07 |
| eClass | 8   | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6   | 27-24-22-07 |
| ETIM   | 10  | EC000236    |
| ETIM   | 9   | EC000236    |
| ETIM   | 8   | EC000236    |
| ETIM   | 7   | EC000236    |
| IDEA   | 4   | 3565        |
| UNSPSC | 15  | 32-15-17-05 |

Approvals / Certificates

|                          |     |
|--------------------------|-----|
| General Product Approval | EMV |
|--------------------------|-----|



[China RoHS](#)



Environment



last modified:

6/16/2025