



Figure similar

SIPLUS S7-1500 CPU 1516F-3 PN/DP based on 6ES7516-3FN02-0AB0 with conformal coating, -40...+60 °C, central processing unit with work memory 1.5 MB for program and 5 MB for data, 1st interface: PROFINET IRT with 2-port switch, 2nd interface: PROFINET RT, 3rd interface: PROFIBUS, 10 ns bit performance, SIMATIC Memory Card required

| General information | |
|---|--|
| Product type designation | CPU 1516F-3 PN/DP |
| based on | 6ES7516-3FN02-0AB0 |
| Product function | |
| <ul style="list-style-type: none"> I&M data Isochronous mode | Yes; I&M0 to I&M3 Yes; Distributed and central; with minimum OB 6x cycle of 375 µs (distributed) and 1 ms (central) |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Configuration control | |
| via dataset | Yes |
| Display | |
| Screen diagonal [cm] | 6.1 cm |
| Control elements | |
| Number of keys | 8 |
| Mode buttons | 2 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time Repeat rate, min. | 5 ms 1/s |
| Input current | |
| Current consumption (rated value) | 0.85 A |
| Current consumption, max. | 1.1 A |
| Inrush current, max. | 2.4 A; Rated value |
| I ² t | 0.02 A ² ·s |
| Power | |
| Infeed power to the backplane bus | 12 W |
| Power consumption from the backplane bus (balanced) | 6.7 W |
| Power loss | |
| Power loss, typ. | 7 W |
| Memory | |
| Number of slots for SIMATIC memory card | 1 |
| SIMATIC memory card required | Yes |
| Work memory | |
| <ul style="list-style-type: none"> integrated (for program) | 1.5 Mbyte |

| | |
|--|---|
| <ul style="list-style-type: none"> integrated (for data) | 5 Mbyte |
| Load memory | |
| <ul style="list-style-type: none"> Plug-in (SIMATIC Memory Card), max. | 32 Gbyte |
| Backup | |
| <ul style="list-style-type: none"> maintenance-free | Yes |
| CPU processing times | |
| for bit operations, typ. | 10 ns |
| for word operations, typ. | 12 ns |
| for fixed point arithmetic, typ. | 16 ns |
| for floating point arithmetic, typ. | 64 ns |
| CPU-blocks | |
| Number of elements (total) | 8 000; Blocks (OB, FB, FC, DB) and UDTs |
| DB | |
| <ul style="list-style-type: none"> Number range | 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999 |
| <ul style="list-style-type: none"> Size, max. | 5 Mbyte; For DBs with absolute addressing, the max. size is 64 KB |
| FB | |
| <ul style="list-style-type: none"> Number range | 0 ... 65 535 |
| <ul style="list-style-type: none"> Size, max. | 1 Mbyte |
| FC | |
| <ul style="list-style-type: none"> Number range | 0 ... 65 535 |
| <ul style="list-style-type: none"> Size, max. | 1 Mbyte |
| OB | |
| <ul style="list-style-type: none"> Size, max. | 1 Mbyte |
| <ul style="list-style-type: none"> Number of free cycle OBs | 100 |
| <ul style="list-style-type: none"> Number of time alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of delay alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of cyclic interrupt OBs | 20; With minimum OB 3x cycle of 250 μs |
| <ul style="list-style-type: none"> Number of process alarm OBs | 50 |
| <ul style="list-style-type: none"> Number of DPV1 alarm OBs | 3 |
| <ul style="list-style-type: none"> Number of isochronous mode OBs | 3 |
| <ul style="list-style-type: none"> Number of technology synchronous alarm OBs | 2 |
| <ul style="list-style-type: none"> Number of startup OBs | 100 |
| <ul style="list-style-type: none"> Number of asynchronous error OBs | 4 |
| <ul style="list-style-type: none"> Number of synchronous error OBs | 2 |
| <ul style="list-style-type: none"> Number of diagnostic alarm OBs | 1 |
| Nesting depth | |
| <ul style="list-style-type: none"> per priority class | 24; Up to 8 possible for F-blocks |
| Counters, timers and their retentivity | |
| S7 counter | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC counter | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| S7 times | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC timer | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 512 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 472 KB |
| Extended retentive data area (incl. timers, counters, flags), max. | 5 Mbyte; When using PS 6 0W 24/48/60 V DC HF |
| Flag | |
| <ul style="list-style-type: none"> Size, max. | 16 kbyte |

| | |
|---|---|
| <ul style="list-style-type: none"> • Number of clock memories | 8; 8 clock memory bit, grouped into one clock memory byte |
| Data blocks | |
| <ul style="list-style-type: none"> • Retentivity adjustable | Yes |
| <ul style="list-style-type: none"> • Retentivity preset | No |
| Local data | |
| <ul style="list-style-type: none"> • per priority class, max. | 64 kbyte; max. 16 KB per block |
| Address area | |
| Number of IO modules | 8 192; max. number of modules / submodules |
| I/O address area | |
| <ul style="list-style-type: none"> • Inputs | 32 kbyte; All inputs are in the process image |
| <ul style="list-style-type: none"> • Outputs | 32 kbyte; All outputs are in the process image |
| per integrated IO subsystem | |
| — Inputs (volume) | 8 kbyte |
| — Outputs (volume) | 8 kbyte |
| per CM/CP | |
| — Inputs (volume) | 8 kbyte |
| — Outputs (volume) | 8 kbyte |
| Subprocess images | |
| <ul style="list-style-type: none"> • Number of subprocess images, max. | 32 |
| Hardware configuration | |
| Number of distributed IO systems | 64; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| Number of DP masters | |
| <ul style="list-style-type: none"> • integrated | 1 |
| <ul style="list-style-type: none"> • Via CM | 8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total |
| Number of IO Controllers | |
| <ul style="list-style-type: none"> • integrated | 2 |
| <ul style="list-style-type: none"> • Via CM | 8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total |
| Rack | |
| <ul style="list-style-type: none"> • Modules per rack, max. | 32; CPU + 31 modules |
| <ul style="list-style-type: none"> • Number of lines, max. | 1 |
| PtP CM | |
| <ul style="list-style-type: none"> • Number of PtP CMs | the number of connectable PtP CMs is only limited by the number of available slots |
| Time of day | |
| Clock | |
| <ul style="list-style-type: none"> • Type | Hardware clock |
| <ul style="list-style-type: none"> • Backup time | 6 wk; At 40 °C ambient temperature, typically |
| <ul style="list-style-type: none"> • Deviation per day, max. | 10 s; Typ.: 2 s |
| Operating hours counter | |
| <ul style="list-style-type: none"> • Number | 16 |
| Clock synchronization | |
| <ul style="list-style-type: none"> • supported | Yes |
| <ul style="list-style-type: none"> • to DP, master | Yes |
| <ul style="list-style-type: none"> • in AS, master | Yes |
| <ul style="list-style-type: none"> • in AS, device | Yes |
| <ul style="list-style-type: none"> • on Ethernet via NTP | Yes |
| Interfaces | |
| Number of PROFINET interfaces | 2 |
| Number of PROFIBUS interfaces | 1 |
| 1. Interface | |
| Interface types | |
| <ul style="list-style-type: none"> • RJ 45 (Ethernet) | Yes; X1 |
| <ul style="list-style-type: none"> • Number of ports | 2 |
| <ul style="list-style-type: none"> • integrated switch | Yes |
| Protocols | |
| <ul style="list-style-type: none"> • IP protocol | Yes; IPv4 |
| <ul style="list-style-type: none"> • PROFINET IO Controller | Yes |
| <ul style="list-style-type: none"> • PROFINET IO Device | Yes |

| | |
|--|--|
| <ul style="list-style-type: none"> • SIMATIC communication • Open IE communication • Web server • Media redundancy | <p>Yes</p> <p>Yes; Optionally also encrypted</p> <p>Yes</p> <p>Yes; MRP Automanager according to IEC 62439-2 Edition 2.0</p> |
| PROFINET IO Controller | |
| Services | |
| — PG/OP communication | Yes |
| — Isochronous mode | Yes |
| — Direct data exchange | Yes; Requirement: IRT and isochronous mode (MRPD optional) |
| — IRT | Yes |
| — PROFINergy | Yes |
| — Prioritized startup | Yes; Max. 32 PROFINET devices |
| — Number of connectable IO Devices, max. | 256; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET |
| — Of which IO devices with IRT, max. | 64 |
| — Number of connectable IO Devices for RT, max. | 256 |
| — of which in line, max. | 256 |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces |
| — Number of IO Devices per tool, max. | 8 |
| — Updating times | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| Update time for IRT | |
| — for send cycle of 250 µs | 250 µs to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 375 µs of the isochronous OB is decisive |
| — for send cycle of 500 µs | 500 µs to 8 ms |
| — for send cycle of 1 ms | 1 ms to 16 ms |
| — for send cycle of 2 ms | 2 ms to 32 ms |
| — for send cycle of 4 ms | 4 ms to 64 ms |
| — With IRT and parameterization of "odd" send cycles | Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3 875 µs) |
| Update time for RT | |
| — for send cycle of 250 µs | 250 µs to 128 ms |
| — for send cycle of 500 µs | 500 µs to 256 ms |
| — for send cycle of 1 ms | 1 ms to 512 ms |
| — for send cycle of 2 ms | 2 ms to 512 ms |
| — for send cycle of 4 ms | 4 ms to 512 ms |
| PROFINET IO Device | |
| Services | |
| — PG/OP communication | Yes |
| — Isochronous mode | No |
| — IRT | Yes |
| — PROFINergy | Yes; per user program |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 4 |
| — Asset management record | Yes; per user program |
| 2. Interface | |
| Interface types | |
| • RJ 45 (Ethernet) | Yes; X2 |
| • Number of ports | 1 |
| • integrated switch | No |
| Protocols | |
| • IP protocol | Yes; IPv4 |
| • PROFINET IO Controller | Yes |
| • PROFINET IO Device | Yes |
| • SIMATIC communication | Yes |
| • Open IE communication | Yes; Optionally also encrypted |
| • Web server | Yes |
| • Media redundancy | No |
| PROFINET IO Controller | |
| Services | |

| | |
|---|--|
| — PG/OP communication | Yes |
| — Isochronous mode | No |
| — Direct data exchange | No |
| — IRT | No |
| — PROFINergy | Yes |
| — Prioritized startup | No |
| — Number of connectable IO Devices, max. | 32; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET |
| — Number of connectable IO Devices for RT, max. | 32 |
| — of which in line, max. | 32 |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces |
| — Number of IO Devices per tool, max. | 8 |
| — Updating times | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |

Update time for RT

| | |
|--------------------------|----------------|
| — for send cycle of 1 ms | 1 ms to 512 ms |
|--------------------------|----------------|

PROFINET IO Device

Services

| | |
|---|-----------------------|
| — PG/OP communication | Yes |
| — Isochronous mode | No |
| — IRT | No |
| — PROFINergy | Yes; per user program |
| — Prioritized startup | No |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 4 |
| — Asset management record | Yes; per user program |

3. Interface

Interface types

| | |
|-------------------|---------|
| ● RS 485 | Yes; X3 |
| ● Number of ports | 1 |

Protocols

| | |
|-------------------------|-----|
| ● PROFIBUS DP master | Yes |
| ● PROFIBUS DP device | No |
| ● SIMATIC communication | Yes |

PROFIBUS DP master

| | |
|-------------------------------|--|
| ● Number of connections, max. | 48; for the integrated PROFIBUS DP interface |
| ● max. number of DP devices | 125; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET |

Services

| | |
|---|-----|
| — PG/OP communication | Yes |
| — Equidistance | Yes |
| — Isochronous mode | Yes |
| — activation/deactivation of DP devices | Yes |

Interface types

RJ 45 (Ethernet)

| | |
|----------------------------------|-----|
| ● 100 Mbps | Yes |
| ● Autonegotiation | Yes |
| ● Autocrossing | Yes |
| ● Industrial Ethernet status LED | Yes |

RS 485

| | |
|---------------------------|-----------|
| ● Transmission rate, max. | 12 Mbit/s |
|---------------------------|-----------|

Protocols

| | |
|-----------|-----|
| PROFIsafe | Yes |
|-----------|-----|

Number of connections

| | |
|---|---|
| ● Number of connections, max. | 256; via integrated interfaces of the CPU and connected CPs / CMs |
| ● Number of connections reserved for ES/HMI/web | 10 |
| ● Number of connections via integrated interfaces | 128 |
| ● Number of S7 routing paths | 16 |

Redundancy mode

| | |
|---------------------|-----|
| ● H-Sync forwarding | Yes |
|---------------------|-----|

| | |
|--|---|
| Media redundancy | |
| — Media redundancy | only via 1st interface (X1) |
| — MRP | Yes; MRP Automanager acc. to IEC 62439-2 Edition 2.0; MRP Manager; MRP Client; max. number of devices in the ring: 50 |
| — MRPD | Yes; Requirement: IRT |
| — Switchover time on line break, typ. | 200 ms; For MRP, bumpless for MRPD |
| — Number of stations in the ring, max. | 50 |
| SIMATIC communication | |
| • S7 routing | Yes |
| • Data record routing | Yes |
| • S7 communication, as server | Yes |
| • S7 communication, as client | Yes |
| • User data per job, max. | See online help (S7 communication, user data size) |
| Open IE communication | |
| • TCP/IP | Yes |
| — Data length, max. | 64 kbyte |
| — several passive connections per port, supported | Yes |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 64 kbyte |
| • UDP | Yes |
| — Data length, max. | 2 kbyte; 1 472 bytes for UDP broadcast |
| — UDP multicast | Yes; Max. 5 multicast circuits |
| • DHCP | No |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Web server | |
| • HTTP | Yes; Standard and user pages |
| • HTTPS | Yes; Standard and user pages |
| OPC UA | |
| • Runtime license required | Yes |
| • OPC UA Client | Yes |
| — Application authentication | Yes |
| — Security policies | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | "anonymous" or by user name & password |
| — Number of connections, max. | 10 |
| — Number of nodes of the client interfaces, recommended max. | 2 000 |
| — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList, max. | 300 |
| — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max. | 20 |
| — Number of elements for one call of OPC-UA_MethodGetHandleList, max. | 100 |
| — Number of simultaneous calls of the client instructions for session management, per connection, max. | 1 |
| — Number of simultaneous calls of the client instructions for data access, per connection, max. | 5 |
| — Number of registerable nodes, max. | 5 000 |
| — Number of registerable method calls of OPC-UA_MethodCall, max. | 100 |
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max. | 20 |
| • OPC UA Server | Yes; Data access (read, write, subscribe), method call, custom address space |
| — Application authentication | Yes |
| — Security policies | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | "anonymous" or by user name & password |
| — Number of sessions, max. | 48 |
| — Number of accessible variables, max. | 100 000 |
| — Number of registerable nodes, max. | 20 000 |
| — Number of subscriptions per session, max. | 20 |

| | |
|--|--|
| — Sampling interval, min. | 100 ms |
| — Publishing interval, min. | 200 ms |
| — Number of server methods, max. | 50 |
| — Number of inputs/outputs per server method, max. | 20 |
| — Number of monitored items, recommended max. | 2 000; for 1 s sampling interval and 1 s send interval |
| — Number of server interfaces, max. | 10; or 20, depending on type of server interface |
| — Number of nodes for user-defined server interfaces, max. | 5 000 |

| | |
|---|--|
| Further protocols | |
| • MODBUS | Yes; MODBUS TCP |
| Isochronous mode | |
| Equidistance | Yes |
| S7 message functions | |
| Number of login stations for message functions, max. | 32 |
| Program alarms | Yes |
| Number of configurable program messages, max. | 10 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH |
| Number of loadable program messages in RUN, max. | 5 000 |
| Number of simultaneously active program alarms | |
| • Number of program alarms | 1 000 |
| • Number of alarms for system diagnostics | 200 |
| • Number of alarms for motion technology objects | 160 |
| Test commissioning functions | |
| Joint commission (Team Engineering) | Yes; Parallel online access possible for up to 8 engineering systems |
| Status block | Yes; Up to 8 simultaneously (in total across all ES clients) |
| Single step | No |
| Number of breakpoints | 8 |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| • Number of variables, max. | |
| — of which status variables, max. | 200; per job |
| — of which control variables, max. | 200; per job |
| Forcing | |
| • Forcing, variables | Peripheral inputs/outputs |
| • Number of variables, max. | 200 |
| Diagnostic buffer | |
| • present | Yes |
| • Number of entries, max. | 3 200 |
| — of which powerfail-proof | 500 |
| Traces | |
| • Number of configurable Traces | 4; Up to 512 KB of data per trace are possible |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| • RUN/STOP LED | Yes |
| • ERROR LED | Yes |
| • MAINT LED | Yes |
| • STOP ACTIVE LED | Yes |
| • Connection display LINK TX/RX | Yes |
| Supported technology objects | |
| Motion Control | Yes; Note: The number of axes affects the cycle time of the PLC program; selection guide via the TIA Selection Tool or SIZER |
| • Number of available Motion Control resources for technology objects | 2 400 |
| • Required Motion Control resources | |
| — per speed-controlled axis | 40 |
| — per positioning axis | 80 |
| — per synchronous axis | 160 |
| — per external encoder | 80 |
| — per output cam | 20 |
| — per cam track | 160 |
| — per probe | 40 |

| | |
|--|---|
| <ul style="list-style-type: none"> Positioning axis <ul style="list-style-type: none"> Number of positioning axes at motion control cycle of 4 ms (typical value) Number of positioning axes at motion control cycle of 8 ms (typical value) | <p>7</p> <p>14</p> |
| Controller <ul style="list-style-type: none"> PID_Compact PID_3Step PID-Temp | <p>Yes; Universal PID controller with integrated optimization</p> <p>Yes; PID controller with integrated optimization for valves</p> <p>Yes; PID controller with integrated optimization for temperature</p> |
| Counting and measuring <ul style="list-style-type: none"> High-speed counter | <p>Yes</p> |
| Standards, approvals, certificates | |
| Highest safety class achievable in safety mode | |
| <ul style="list-style-type: none"> Performance level according to ISO 13849-1 SIL acc. to IEC 61508 | <p>PLe</p> <p>SIL 3</p> |
| Probability of failure (for service life of 20 years and repair time of 100 hours) | |
| <ul style="list-style-type: none"> Low demand mode: PFDavg in accordance with SIL3 High demand/continuous mode: PFH in accordance with SIL3 | <p>< 2.00E-05</p> <p>< 1.00E-09</p> |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. | <p>-40 °C; = Tmin (incl. condensation/frost)</p> <p>60 °C; = Tmax; display: 50 °C, the display is switched off at an operating temperature of typically 50 °C</p> <p>-40 °C; = Tmin</p> <p>40 °C; = Tmax; display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off</p> |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. max. | <p>-40 °C</p> <p>70 °C</p> |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. Ambient air temperature-barometric pressure-altitude | <p>5 000 m; Restrictions for installation altitudes > 2 000 m, see manual</p> <p>Restrictions for installation altitudes > 2 000 m, see entry ID: 109763260</p> |
| Relative humidity | |
| <ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. | <p>100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation</p> |
| Resistance | |
| Coolants and lubricants | |
| <ul style="list-style-type: none"> Resistant to commercially available coolants and lubricants | <p>Yes; Incl. diesel and oil droplets in the air</p> |
| Use in stationary industrial systems | |
| <ul style="list-style-type: none"> to biologically active substances according to EN 60721-3-3 to chemically active substances according to EN 60721-3-3 to mechanically active substances according to EN 60721-3-3 | <p>Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request</p> <p>Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 3S4 incl. sand, dust, *</p> |
| Use on ships/at sea | |
| <ul style="list-style-type: none"> to biologically active substances according to EN 60721-3-6 to chemically active substances according to EN 60721-3-6 to mechanically active substances according to EN 60721-3-6 | <p>Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)</p> <p>Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *</p> <p>Yes; Class 6S3 incl. sand, dust; *</p> |
| Usage in industrial process technology | |
| <ul style="list-style-type: none"> Against chemically active substances acc. to EN 60654-4 Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | <p>Yes; Class 3 (excluding trichlorethylene)</p> <p>Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)</p> |
| Remark | |
| <ul style="list-style-type: none"> Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | <p>* The supplied plug covers must remain in place over the unused interfaces during operation!</p> |
| Conformal coating | |

- Coatings for printed circuit board assemblies acc. to EN 61086
- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Class 2 for high reliability
 Yes; Type 1 protection
 Yes; Discoloration of coating possible during service life
 Yes; Conformal coating, Class A

configuration / header

configuration / programming / header

| | |
|----------------------|---------------------|
| Programming language | |
| — LAD | Yes; incl. failsafe |
| — FBD | Yes; incl. failsafe |
| — STL | Yes |
| — SCL | Yes |
| — GRAPH | Yes |

| | |
|---|-----|
| Know-how protection | |
| • User program protection/password protection | Yes |
| • Copy protection | Yes |
| • Block protection | Yes |

| | |
|---|---|
| Access protection | |
| • Password for display | Yes |
| • Protection level: Write protection | Yes; Specific write protection both for Standard and for Failsafe |
| • Protection level: Read/write protection | Yes |
| • Protection level: Complete protection | Yes |

| | |
|--|-------------------------------|
| programming / cycle time monitoring / header | |
| • lower limit | adjustable minimum cycle time |
| • upper limit | adjustable maximum cycle time |

| | |
|-------------------|--------|
| Dimensions | |
| Width | 70 mm |
| Height | 147 mm |
| Depth | 129 mm |

| | |
|-----------------|-------|
| Weights | |
| Weight, approx. | 560 g |

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 10 | EC000236 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

| | |
|--------------------------|-----|
| General Product Approval | EMV |
|--------------------------|-----|

[Manufacturer Declaration](#)



[China RoHS](#)



| | | |
|--------------------------------|-------------------|----------------------|
| For use in hazardous locations | Functional Safety | Maritime application |
|--------------------------------|-------------------|----------------------|



last modified:

7/1/2025