



Figure similar

SIPLUS S7-1500 CPU 1516-3 PN rail based on 6ES7516-3AP03-0AB0 with conformal coating OT4: -40...+70 °C ST1/2: 85 °C for 10 minutes . central processing unit with 2 MB work memory for program and 7.5 MB for data 1st interface: PROFINET IRT with 2-port switch, 2nd interface: PROFINET RT, 3rd interface: PROFIBUS, 6 ns bit performance, SIMATIC Memory Card required

| General information                                      |   |
|--|---|
| Product type designation                                 | CPU 1516-3 PN/DP  |
| Firmware version   |   |
| • FW update possible                                     | Yes   |
| based on   | <a href="#">6ES7516-3AP03-0AB0</a>  |
| Product function   |   |
| • I&M data   | Yes; I&M0 to I&M3   |
| • Isochronous mode                                       | Yes; Distributed and central; with minimum OB 6x cycle of 375 µs (distributed) and 1 ms (central) |
| Engineering with   |   |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275   |
| Configuration control                                    |   |
| via dataset  | Yes   |
| Display  |   |
| Screen diagonal [cm]                                     | 6.1 cm  |
| Control elements   |   |
| Number of keys   | 8   |
| Mode buttons   | 2   |
| Supply voltage   |   |
| Rated value (DC)   | 24 V  |
| permissible range, lower limit (DC)                      | 19.2 V  |
| permissible range, upper limit (DC)                      | 28.8 V  |
| Reverse polarity protection                              | Yes   |
| Mains buffering  |   |
| • Mains/voltage failure stored energy time               | 5 ms  |
| • Repeat rate, min.                                      | 1/s   |
| Input current  |   |
| Current consumption (rated value)                        | 0.87 A  |
| Current consumption, max.                                | 1.08 A  |
| Inrush current, max.                                     | 1.15 A; Rated value   |
| I <sup>2</sup> t   | 0.6 A <sup>2</sup> ·s   |
| Power  |   |
| Infeed power to the backplane bus                        | 12 W  |
| Power consumption from the backplane bus (balanced)      | 6.7 W   |
| Power loss   |   |
| Power loss, typ.   | 4 W   |
| Memory   |   |
| Number of slots for SIMATIC memory card                  | 1   |
| SIMATIC memory card required                             | Yes   |

|  |   |
|--|---|
| <b>Work memory</b>   |   |
| • integrated (for program)   | 2 Mbyte   |
| • integrated (for data)  | 7.5 Mbyte   |
| <b>Load memory</b>   |   |
| • Plug-in (SIMATIC Memory Card), max.                              | 32 Gbyte  |
| <b>Backup</b>  |   |
| • maintenance-free   | Yes   |
| <b>CPU processing times</b>  |   |
| for bit operations, typ.   | 6 ns  |
| for word operations, typ.  | 7 ns  |
| for fixed point arithmetic, typ.                                   | 9 ns  |
| for floating point arithmetic, typ.                                | 37 ns   |
| <b>CPU-blocks</b>  |   |
| Number of elements (total)   | 8 000; Blocks (OB, FB, FC, DB) and UDTs   |
| <b>DB</b>  |   |
| • Number range   | 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999 |
| • Size, max.   | 7.5 Mbyte; For DBs with absolute addressing, the max. size is 64 KB   |
| <b>FB</b>  |   |
| • Number range   | 0 ... 65 535  |
| • Size, max.   | 1 Mbyte   |
| <b>FC</b>  |   |
| • Number range   | 0 ... 65 535  |
| • Size, max.   | 1 Mbyte   |
| <b>OB</b>  |   |
| • Size, max.   | 1 Mbyte   |
| • Number of free cycle OBs   | 100   |
| • Number of time alarm OBs   | 20  |
| • Number of delay alarm OBs  | 20  |
| • Number of cyclic interrupt OBs                                   | 20; With minimum OB 3x cycle of 250 µs  |
| • Number of process alarm OBs                                      | 50  |
| • Number of DPV1 alarm OBs   | 3   |
| • Number of isochronous mode OBs                                   | 3   |
| • Number of technology synchronous alarm OBs                       | 2   |
| • Number of startup OBs  | 100   |
| • Number of asynchronous error OBs                                 | 4   |
| • Number of synchronous error OBs                                  | 2   |
| • Number of diagnostic alarm OBs                                   | 1   |
| <b>Nesting depth</b>   |   |
| • per priority class   | 24  |
| <b>Counters, timers and their retentivity</b>                      |   |
| <b>S7 counter</b>  |   |
| • Number   | 2 048   |
| Retentivity  |   |
| — adjustable   | Yes   |
| <b>IEC counter</b>   |   |
| • Number   | Any (only limited by the main memory)   |
| Retentivity  |   |
| — adjustable   | Yes   |
| <b>S7 times</b>  |   |
| • Number   | 2 048   |
| Retentivity  |   |
| — adjustable   | Yes   |
| <b>IEC timer</b>   |   |
| • Number   | Any (only limited by the main memory)   |
| Retentivity  |   |
| — adjustable   | Yes   |
| <b>Data areas and their retentivity</b>                            |   |
| Retentive data area (incl. timers, counters, flags), max.          | 512 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 472 KB                           |
| Extended retentive data area (incl. timers, counters, flags), max. | 7.5 Mbyte; When using PS 6 0W 24/48/60 V DC HF  |

|  |   |
|--|---|
| <b>Flag</b>  |   |
| <ul style="list-style-type: none"> <li>• Size, max.</li> <li>• Number of clock memories</li> </ul>   | <p>16 kbyte<br/>8; 8 clock memory bit, grouped into one clock memory byte</p>   |
| <b>Data blocks</b>   |   |
| <ul style="list-style-type: none"> <li>• Retentivity adjustable</li> <li>• Retentivity preset</li> </ul>   | <p>Yes<br/>No</p>   |
| <b>Local data</b>  |   |
| <ul style="list-style-type: none"> <li>• per priority class, max.</li> </ul>   | 64 kbyte; max. 16 KB per block  |
| <b>Address area</b>  |   |
| Number of IO modules   | 8 192; max. number of modules / submodules  |
| <b>I/O address area</b>  |   |
| <ul style="list-style-type: none"> <li>• Inputs</li> <li>• Outputs</li> </ul>  | <p>32 kbyte; All inputs are in the process image<br/>32 kbyte; All outputs are in the process image</p>   |
| per integrated IO subsystem  |   |
| — Inputs (volume)  | 8 kbyte   |
| — Outputs (volume)   | 8 kbyte   |
| per CM/CP  |   |
| — Inputs (volume)  | 8 kbyte   |
| — Outputs (volume)   | 8 kbyte   |
| <b>Subprocess images</b>   |   |
| <ul style="list-style-type: none"> <li>• Number of subprocess images, max.</li> </ul>  | 32  |
| <b>Hardware configuration</b>  |   |
| Number of distributed IO systems   | 64; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| <b>Number of DP masters</b>  |   |
| <ul style="list-style-type: none"> <li>• integrated</li> <li>• Via CM</li> </ul>   | <p>1<br/>8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total</p>  |
| <b>Number of IO Controllers</b>  |   |
| <ul style="list-style-type: none"> <li>• integrated</li> <li>• Via CM</li> </ul>   | <p>2<br/>8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total</p>  |
| <b>Rack</b>  |   |
| <ul style="list-style-type: none"> <li>• Modules per rack, max.</li> <li>• Number of lines, max.</li> </ul>  | <p>32; CPU + 31 modules<br/>1</p>   |
| <b>PtP CM</b>  |   |
| <ul style="list-style-type: none"> <li>• Number of PtP CMs</li> </ul>  | the number of connectable PtP CMs is only limited by the number of available slots  |
| <b>Time of day</b>   |   |
| <b>Clock</b>   |   |
| <ul style="list-style-type: none"> <li>• Type</li> <li>• Backup time</li> <li>• Deviation per day, max.</li> </ul>   | <p>Hardware clock<br/>6 wk; At 40 °C ambient temperature, typically<br/>10 s; Typ.: 2 s</p>   |
| <b>Operating hours counter</b>   |   |
| <ul style="list-style-type: none"> <li>• Number</li> </ul>   | 16  |
| <b>Clock synchronization</b>   |   |
| <ul style="list-style-type: none"> <li>• supported</li> <li>• to DP, master</li> <li>• on DP, device</li> <li>• in AS, master</li> <li>• in AS, device</li> <li>• on Ethernet via NTP</li> </ul> | <p>Yes<br/>Yes<br/>Yes; via PROFIBUS CM / CP<br/>Yes<br/>Yes<br/>Yes</p>  |
| <b>Interfaces</b>  |   |
| Number of PROFINET interfaces  | 2   |
| Number of PROFIBUS interfaces  | 1   |
| <b>1. Interface</b>  |   |
| <b>Interface types</b>   |   |
| <ul style="list-style-type: none"> <li>• RJ 45 (Ethernet)</li> <li>• Number of ports</li> <li>• integrated switch</li> </ul>   | <p>Yes; X1<br/>2<br/>Yes</p>  |
| <b>Protocols</b>   |   |

|   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• IP protocol</li> <li>• PROFINET IO Controller</li> <li>• PROFINET IO Device</li> <li>• SIMATIC communication</li> <li>• Open IE communication</li> <li>• Web server</li> <li>• Media redundancy</li> </ul> | <p>Yes; IPv4</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Optionally also encrypted</p> <p>Yes</p> <p>Yes</p>  |
| <b>PROFINET IO Controller</b>   |  |
| <b>Services</b>   |  |
| — Isochronous mode  | Yes  |
| — Direct data exchange  | Yes; Requirement: IRT and isochronous mode (MRPD optional)   |
| — IRT   | Yes  |
| — PROFINergy  | Yes; per user program  |
| — Prioritized startup   | Yes; Max. 32 PROFINET devices  |
| — Number of connectable IO Devices, max.  | 256; in total, up to 1024 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET  |
| — Of which IO devices with IRT, max.  | 64   |
| — Number of connectable IO Devices for RT, max.   | 256  |
| — of which in line, max.  | 256  |
| — Number of IO Devices that can be simultaneously activated/deactivated, max.   | 8; in total across all interfaces  |
| — Number of IO Devices per tool, max.   | 8  |
| — Updating times  | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| — PROFINET Security Class   | 1  |
| <b>Update time for IRT</b>  |  |
| — for send cycle of 250 µs  | 250 µs to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 375 µs of the isochronous OB is decisive                                    |
| — for send cycle of 500 µs  | 500 µs to 8 ms   |
| — for send cycle of 1 ms  | 1 ms to 16 ms  |
| — for send cycle of 2 ms  | 2 ms to 32 ms  |
| — for send cycle of 4 ms  | 4 ms to 64 ms  |
| — With IRT and parameterization of "odd" send cycles  | Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3 875 µs)   |
| <b>Update time for RT</b>   |  |
| — for send cycle of 250 µs  | 250 µs to 128 ms   |
| — for send cycle of 500 µs  | 500 µs to 256 ms   |
| — for send cycle of 1 ms  | 1 ms to 512 ms   |
| — for send cycle of 2 ms  | 2 ms to 512 ms   |
| — for send cycle of 4 ms  | 4 ms to 512 ms   |
| <b>PROFINET IO Device</b>   |  |
| <b>Services</b>   |  |
| — Isochronous mode  | No   |
| — IRT   | Yes  |
| — PROFINergy  | Yes; per user program  |
| — Shared device   | Yes  |
| — Number of IO Controllers with shared device, max.   | 4  |
| — activation/deactivation of I-devices  | Yes; per user program  |
| — Asset management record   | Yes; per user program  |
| — PROFINET Security Class   | SNMP Configuration and DCP Read Only   |
| <b>2. Interface</b>   |  |
| <b>Interface types</b>  |  |
| <ul style="list-style-type: none"> <li>• RJ 45 (Ethernet)</li> <li>• Number of ports</li> <li>• integrated switch</li> </ul>  | <p>Yes; X2</p> <p>1</p> <p>No</p>  |
| <b>Protocols</b>  |  |
| <ul style="list-style-type: none"> <li>• IP protocol</li> <li>• PROFINET IO Controller</li> <li>• PROFINET IO Device</li> <li>• SIMATIC communication</li> <li>• Open IE communication</li> </ul>   | <p>Yes; IPv4</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Optionally also encrypted</p>  |

|   |  |
|---|--|
| • Web server  | Yes  |
| • Media redundancy  | No   |
| <b>PROFINET IO Controller</b>   |  |
| <b>Services</b>   |  |
| — Isochronous mode  | No   |
| — Direct data exchange  | No   |
| — IRT   | No   |
| — PROFINergy  | Yes; per user program  |
| — Prioritized startup   | No   |
| — Number of connectable IO Devices, max.                                      | 32; in total, up to 1024 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET   |
| — Number of connectable IO Devices for RT, max.                               | 32   |
| — of which in line, max.  | 32   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces  |
| — Number of IO Devices per tool, max.   | 8  |
| — Updating times  | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| — PROFINET Security Class   | 1  |
| <b>Update time for RT</b>   |  |
| — for send cycle of 1 ms  | 1 ms to 512 ms   |
| <b>PROFINET IO Device</b>   |  |
| <b>Services</b>   |  |
| — Isochronous mode  | No   |
| — IRT   | No   |
| — PROFINergy  | Yes; per user program  |
| — Prioritized startup   | No   |
| — Shared device   | Yes  |
| — Number of IO Controllers with shared device, max.                           | 4  |
| — activation/deactivation of I-devices  | Yes; per user program  |
| — Asset management record   | Yes; per user program  |
| — PROFINET Security Class   | SNMP Configuration and DCP Read Only   |
| <b>3. Interface</b>   |  |
| <b>Interface types</b>  |  |
| • RS 485  | Yes; X3  |
| • Number of ports   | 1  |
| <b>Protocols</b>  |  |
| • PROFIBUS DP master  | Yes  |
| • PROFIBUS DP device  | No   |
| • SIMATIC communication   | Yes  |
| <b>PROFIBUS DP master</b>   |  |
| • Number of connections, max.   | 48; for the integrated PROFIBUS DP interface   |
| • max. number of DP devices   | 125; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET   |
| <b>Services</b>   |  |
| — Equidistance  | Yes  |
| — Isochronous mode  | Yes  |
| — activation/deactivation of DP devices                                       | Yes  |
| <b>Interface types</b>  |  |
| <b>RJ 45 (Ethernet)</b>   |  |
| • 100 Mbps  | Yes  |
| • Autonegotiation   | Yes  |
| • Autocrossing  | Yes  |
| • Industrial Ethernet status LED  | Yes  |
| <b>RS 485</b>   |  |
| • Transmission rate, max.   | 12 Mbit/s  |
| <b>Protocols</b>  |  |
| PROFIsafe   | No   |
| <b>Number of connections</b>  |  |
| • Number of connections, max.   | 256; via integrated interfaces of the CPU and connected CPs / CMs  |
| • Number of connections reserved for ES/HMI/web                               | 10   |

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Number of connections via integrated interfaces</li> </ul>    | 128  |
| <ul style="list-style-type: none"> <li>• Number of S7 routing paths</li> </ul>                         | 16   |
| <b>Redundancy mode</b>   |  |
| <ul style="list-style-type: none"> <li>• H-Sync forwarding</li> </ul>                                  | Yes  |
| <b>Media redundancy</b>  |  |
| — Media redundancy   | only via 1st interface (X1)  |
| — MRP  | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0, MRP Manager; MRP Client |
| — MRP interconnection, supported   | Yes; as MRP ring node according to IEC 62439-2 Edition 3.0                         |
| — MRPD   | Yes; Requirement: IRT  |
| — Switchover time on line break, typ.  | 200 ms; For MRP, bumpless for MRPD   |
| — Number of stations in the ring, max.   | 50   |
| <b>SIMATIC communication</b>   |  |
| <ul style="list-style-type: none"> <li>• PG/OP communication</li> </ul>                                | Yes; encryption with TLS V1.3 pre-selected   |
| <ul style="list-style-type: none"> <li>• S7 routing</li> </ul>   | Yes  |
| <ul style="list-style-type: none"> <li>• Data record routing</li> </ul>                                | Yes  |
| <ul style="list-style-type: none"> <li>• S7 communication, as server</li> </ul>                        | Yes  |
| <ul style="list-style-type: none"> <li>• S7 communication, as client</li> </ul>                        | Yes  |
| <ul style="list-style-type: none"> <li>• User data per job, max.</li> </ul>                            | See online help (S7 communication, user data size)                                 |
| <b>Open IE communication</b>   |  |
| <ul style="list-style-type: none"> <li>• TCP/IP</li> </ul>   | Yes  |
| — Data length, max.  | 64 kbyte   |
| — several passive connections per port, supported  | Yes  |
| <ul style="list-style-type: none"> <li>• ISO-on-TCP (RFC1006)</li> </ul>                               | Yes  |
| — Data length, max.  | 64 kbyte   |
| <ul style="list-style-type: none"> <li>• UDP</li> </ul>  | Yes  |
| — Data length, max.  | 2 kbyte; 1 472 bytes for UDP broadcast   |
| — UDP multicast  | Yes; max. 118 multicast circuits   |
| <ul style="list-style-type: none"> <li>• DHCP</li> </ul>   | Yes  |
| <ul style="list-style-type: none"> <li>• DNS</li> </ul>  | Yes  |
| <ul style="list-style-type: none"> <li>• SNMP</li> </ul>   | Yes  |
| <ul style="list-style-type: none"> <li>• DCP</li> </ul>  | Yes  |
| <ul style="list-style-type: none"> <li>• LLDP</li> </ul>   | Yes  |
| <ul style="list-style-type: none"> <li>• Encryption</li> </ul>   | Yes; Optional  |
| <b>Web server</b>  |  |
| <ul style="list-style-type: none"> <li>• HTTP</li> </ul>   | Yes; Standard and user pages   |
| <ul style="list-style-type: none"> <li>• HTTPS</li> </ul>  | Yes; Standard and user pages   |
| <ul style="list-style-type: none"> <li>• web API</li> </ul>  |  |
| — Number of sessions, max.   | 100  |
| — number of simultaneous HTTP calls, max.  | 4  |
| — HTTP request body, max.  | 131 072 byte   |
| <b>OPC UA</b>  |  |
| <ul style="list-style-type: none"> <li>• Runtime license required</li> </ul>                           | Yes; "Medium" license required   |
| <ul style="list-style-type: none"> <li>• OPC UA Client</li> </ul>                                      | Yes; Data Access (registered Read/Write), Method Call                              |
| — Application authentication   | Yes  |
| — Security policies  | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256    |
| — User authentication  | "anonymous" or by user name & password   |
| — Number of connections, max.  | 10   |
| — Number of nodes of the client interfaces, recommended max.   | 2 000  |
| — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList, max.   | 300  |
| — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max.                                | 20   |
| — Number of elements for one call of OPC-UA_MethodGetHandleList, max.                                  | 100  |
| — Number of simultaneous calls of the client instructions for session management, per connection, max. | 1  |
| — Number of simultaneous calls of the client instructions for data access, per connection, max.        | 5  |
| — Number of registerable nodes, max.   | 5 000  |

|  |   |
|--|---|
| — Number of registerable method calls of OPC-UA_MethodCall, max. | 100   |
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max.  | 20  |
| ● OPC UA Server  | Yes; data access (read, write, subscribe), method call, alarms & condition (A&C), custom address space, role-based access control |
| — Application authentication                                     | Yes   |
| — Security policies  | available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256, Aes128Sha256RsaOaep, Aes256Sha256RsaPss          |
| — User authentication  | "anonymous" or by user name & password  |
| — GDS support (certificate management)                           | Yes   |
| — Number of sessions, max.                                       | 48  |
| — Number of accessible variables, max.                           | 100 000   |
| — Number of registerable nodes, max.                             | 20 000  |
| — Number of subscriptions per session, max.                      | 50  |
| — Sampling interval, min.  | 100 ms  |
| — Publishing interval, min.                                      | 100 ms  |
| — Number of server methods, max.                                 | 50; max. 20 concurrently running jobs each for asynchronous instructions OPC-UA_ServerMethodPre and OPC-UA_ServerMethodPost       |
| — Number of inputs/outputs per server method, max.               | 20  |
| — Number of monitored items, recommended max.                    | 4 000; for 1 s sampling interval and 1 s send interval  |
| — Number of server interfaces, max.                              | 10 of each "Server interfaces" / "Companion specification" type and 20 of the type "Reference namespace"                          |
| — Number of nodes for user-defined server interfaces, max.       | 30 000  |
| ● Alarms and Conditions  | Yes   |
| — Number of program alarms                                       | 200   |
| — Number of alarms for system diagnostics                        | 100   |
| <b>Further protocols</b>   |   |
| ● MODBUS   | Yes; MODBUS TCP   |
| <b>Isochronous mode</b>  |   |
| Equidistance   | Yes   |
| <b>S7 message functions</b>                                      |   |
| Number of login stations for message functions, max.             | 64  |
| number of subscriptions, max.                                    | 500   |
| number of tags/attributes for subscriptions, max.                | 8 000   |
| Program alarms   | Yes   |
| Number of configurable program messages, max.                    | 10 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH   |
| Number of loadable program messages in RUN, max.                 | 10 000  |
| Number of simultaneously active program alarms                   |   |
| ● Number of program alarms                                       | 1 000   |
| ● Number of alarms for system diagnostics                        | 200   |
| ● Number of alarms for motion technology objects                 | 160   |
| <b>Test commissioning functions</b>                              |   |
| Joint commission (Team Engineering)                              | Yes; Parallel online access possible for up to 8 engineering systems  |
| Status block   | Yes; Up to 8 simultaneously (in total across all ES clients)  |
| Single step  | No  |
| Number of breakpoints  | 8   |
| Profiling  | Yes   |
| <b>Status/control</b>  |   |
| ● Status/control variable  | Yes   |
| ● Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters  |
| ● Number of variables, max.                                      |   |
| — of which status variables, max.                                | 200; per job  |
| — of which control variables, max.                               | 200; per job  |
| <b>Forcing</b>   |   |
| ● Forcing  | Yes   |
| ● Forcing, variables   | Peripheral inputs/outputs   |
| ● Number of variables, max.                                      | 200   |
| <b>Diagnostic buffer</b>   |   |
| ● present  | Yes   |
| ● Number of entries, max.  | 3 200   |

|  |  |
|--|--|
| — of which powerfail-proof   | 500  |
| <b>Traces</b>  |  |
| • Number of configurable Traces  | 4  |
| • Memory size per trace, max.  | 512 kbyte  |
| <b>Interrupts/diagnostics/status information</b>                             |  |
| <b>Diagnostics indication LED</b>  |  |
| • RUN/STOP LED   | Yes  |
| • ERROR LED  | Yes  |
| • MAINT LED  | Yes  |
| • STOP ACTIVE LED  | Yes  |
| • Connection display LINK TX/RX  | Yes  |
| <b>Supported technology objects</b>  |  |
| Motion Control   | Yes; Note: The number of technology objects affects the cycle time of the PLC program; selection guide via the TIA Selection Tool                            |
| • Number of available Motion Control resources for technology objects        | 2 400  |
| • Required Motion Control resources  |  |
| — per speed-controlled axis  | 40   |
| — per positioning axis   | 80   |
| — per synchronous axis   | 160  |
| — per external encoder   | 80   |
| — per output cam   | 20   |
| — per cam track  | 160  |
| — per probe  | 40   |
| • Positioning axis   |  |
| — Number of positioning axes at motion control cycle of 4 ms (typical value) | 11   |
| — Number of positioning axes at motion control cycle of 8 ms (typical value) | 20   |
| Controller   |  |
| • PID_Compact  | Yes; Universal PID controller with integrated optimization   |
| • PID_3Step  | Yes; PID controller with integrated optimization for valves  |
| • PID-Temp   | Yes; PID controller with integrated optimization for temperature   |
| Counting and measuring   |  |
| • High-speed counter   | Yes  |
| <b>Isolation</b>   |  |
| Isolation tested with  | 750 V DC (type test) and according to EN 50155 (routine test); internal voltage limitation between internal chassis and ground to $\pm 300$ V (varistor)     |
| <b>Standards, approvals, certificates</b>                                    |  |
| <b>Ecological footprint</b>  |  |
| • environmental product declaration  | Yes  |
| <b>Global warming potential</b>  |  |
| — global warming potential, (total) [CO2 eq]                                 | 102 kg   |
| — global warming potential, (during production) [CO2 eq]                     | 26.5 kg  |
| — global warming potential, (during operation) [CO2 eq]                      | 76.7 kg  |
| — global warming potential, (after end of life cycle) [CO2 eq]               | -0.898 kg  |
| <b>Railway application</b>   |  |
| • EN 50121-3-2   | Yes; EMC for rail vehicles   |
| • EN 50121-4   | Yes; EMC for signal and telecommunications systems   |
| • EN 50121-5   | Yes; EMC for fixed installations and railway power supply equipment  |
| • EN 50124-1   | Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC                                  |
| • EN 50125-1   | Yes; Rail vehicles - see ambient conditions  |
| • EN 50125-2   | Yes; Stationary electrical equipment - see ambient conditions  |
| • EN 50125-3   | Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track) |
| • EN 50155   | Yes; Rail vehicles - temperature class OT4, ST1/ST2, horizontal mounting position  |
| • EN 61373   | Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B   |
| • Fire protection acc. to EN 45545-2   | Yes; For proof of conformity, see Service & Support  |

**product functions / security / header**

|                         |     |
|-------------------------|-----|
| PROFINET Security Class | 1   |
| signed firmware update  | Yes |
| Secure Boot             | Yes |
| safely removing data    | Yes |

**Ambient conditions**

|  |   |
|--|---|
| <b>Ambient temperature during operation</b>  |   |
| <ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul> | -40 °C; = Tmin (incl. condensation/frost)<br>70 °C; = Tmax; +85 °C for 10 min (OT4, ST1/ST2 acc. to EN 50155); display: 50 °C, the display is switched off at an operating temperature of typically 50 °C<br>-40 °C; = Tmin<br>40 °C; = Tmax; display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off |

|  |                 |
|--|-----------------|
| <b>Ambient temperature during storage/transportation</b>             |                 |
| <ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul> | -40 °C<br>70 °C |

|   |   |
|---|---|
| <b>Altitude during operation relating to sea level</b>  |   |
| <ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> <li>Ambient air temperature-barometric pressure-altitude</li> </ul> | 2 000 m<br>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |

|   |   |
|---|---|
| <b>Relative humidity</b>  |   |
| <ul style="list-style-type: none"> <li>With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul> | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |

**Resistance**

|   |   |
|---|---|
| <b>Coolants and lubricants</b>                                |   |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |

|   |  |
|---|--|
| <b>Use in stationary industrial systems</b>                   |  |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *           |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, *   |

|  |  |
|--|--|
| <b>Use on land craft, rail vehicles and special-purpose vehicles</b> |  |
| — to biologically active substances according to EN 60721-3-5        | Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request |
| — to chemically active substances according to EN 60721-3-5          | Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *           |
| — to mechanically active substances according to EN 60721-3-5        | Yes; Class 5S3 incl. sand, dust; *   |

|  |   |
|--|---|
| <b>Usage in industrial process technology</b>  |   |
| — Against chemically active substances acc. to EN 60654-4                                    | Yes; Class 3 (excluding trichlorethylene)   |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |

|   |  |
|---|--|
| <b>Remark</b>   |  |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |

|   |  |
|---|--|
| <b>Conformal coating</b>  |  |
| <ul style="list-style-type: none"> <li>Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>Protection against fouling acc. to EN 60664-3</li> <li>Electronic equipment on rolling stock acc. to EN 50155</li> <li>Military testing according to MIL-I-46058C, Amendment 7</li> <li>Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul> | Yes; Class 2 for high reliability<br>Yes; Type 1 protection<br>Yes; class PC2 protective coating acc. to EN 50155<br>Yes; Discoloration of coating possible during service life<br>Yes; Conformal coating, Class A |

**configuration / header**

|   |     |
|---|-----|
| <b>configuration / programming / header</b> |     |
| <b>Programming language</b>                 |     |
| — LAD                                       | Yes |
| — FBD                                       | Yes |
| — STL                                       | Yes |
| — SCL                                       | Yes |

|   |  |
|---|--|
| — CFC   | Yes  |
| — GRAPH   | Yes  |
| <b>Know-how protection</b>                          |  |
| • User program protection/password protection       | Yes  |
| • Copy protection                                   | Yes  |
| • Block protection                                  | Yes  |
| <b>Access protection</b>                            |  |
| • protection of confidential configuration data     | Yes  |
| • Password for display                              | Yes  |
| • Protection level: Write protection                | Yes  |
| • Protection level: Read/write protection           | Yes  |
| • Protection level: Write protection for Failsafe   | No   |
| • Protection level: Complete protection             | Yes  |
| • User administration                               | Yes; device-wide and centralized   |
| • Number of users                                   | 100  |
| • Number of groups                                  | 100  |
| • Number of roles                                   | 50   |
| <b>programming / cycle time monitoring / header</b> |  |
| • lower limit                                       | adjustable minimum cycle time  |
| • upper limit                                       | adjustable maximum cycle time  |
| <b>Dimensions</b>                                   |  |
| Width   | 70 mm  |
| Height  | 147 mm   |
| Depth   | 129 mm   |
| <b>Weights</b>                                      |  |
| Weight, approx.                                     | 545 g  |
| <b>Other</b>  |  |
| Note:   | for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776 |

| <b>Classifications</b> |        |                |                       |
|------------------------|--------|----------------|-----------------------|
|                        |        | <b>Version</b> | <b>Classification</b> |
|                        | eClass | 14             | 27-24-22-07           |
|                        | eClass | 12             | 27-24-22-07           |
|                        | eClass | 9.1            | 27-24-22-07           |
|                        | eClass | 9              | 27-24-22-07           |
|                        | eClass | 8              | 27-24-22-07           |
|                        | eClass | 7.1            | 27-24-22-07           |
|                        | eClass | 6              | 27-24-22-07           |
|                        | ETIM   | 10             | EC000236              |
|                        | ETIM   | 9              | EC000236              |
|                        | ETIM   | 8              | EC000236              |
|                        | ETIM   | 7              | EC000236              |
|                        | IDEA   | 4              | 3565                  |
|                        | UNSPSC | 15             | 32-15-17-05           |

|                                 |     |
|---------------------------------|-----|
| <b>Approvals / Certificates</b> |     |
| General Product Approval        | EMV |



[China RoHS](#)



|                |                    |
|----------------|--------------------|
| <b>Railway</b> | <b>Environment</b> |
|----------------|--------------------|

[Confirmation](#)



---

last modified:

7/1/2025 