

CONNECT. MOD. TPRI 110V SCREW TERM.

Connection module TPRI with relay 110 V AC, Output 8 NO contacts 24V DC/0.05 A Type: Screw terminal with LED, VPE=1 unit 16 pole IDC connector f. cable



target system	SIMATIC S7-300 / 1500
suitability for use	Digital input module
product type designation	Fully modular connection
product designation	Connection module
<b>electrical data</b>	
operating voltage	
• at AC / rated value	110 V; for coil
ampacity / per pin / maximum	1 A
continuous current / at DC / per signal cable / maximum	0.05 A
switching capacity current / of the contacts / with resistive load / maximum	0.05 A; for 24V AC; recommended minimal load larger than 5mA
relay design	For input signals
type of switching contact	Single contact, NO contact
number of relay outputs	8
operating frequency / maximum	8.33 1/s
mechanical service life (operating cycles) / typical	10 000 000
electrical endurance (operating cycles) / typical	3 000 000; for AC 230 V/50 mA/Cos phi = 1
display version	
• as status display of the inputs/outputs	LED yellow for "active high"
• for power supply / power LED	Yes; green for 24 V DC O.K.
product function / infeed function	Yes
product component	
• PE connection	No
• shield connection	No
• disconnecter	No
• protective wiring	No
product feature / cross-connectable	No
<b>connection method</b>	
number of terminals	20; 8 x I x 2; 2 x L+, 2 x M
number of channels	8
type of connecting terminal	Screw-type terminal
position / of the terminal	Top
number of terminal levels	1
design of terminal / terminal levels internally linked	No
type of electrical connection / for connecting cable	Plug-in connection
number of poles / at the 1st interface	16; IDC connector with installed strain relief for the connecting cable
number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	

<ul style="list-style-type: none"><li>• for flexible conductor / with core end processing</li><li>• stranded</li><li>• finely stranded / with core end processing</li></ul>	0.5 ... 2.5 mm²; End sleeve according to DIN 46228/1		
	0.5 ... 2.5 mm²		
	0.5 ... 2.5 mm²		
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.		
width of screwdriver blade	3.5 mm		
tightening torque	0.4 ... 0.5 N·m		
standards, specifications, approvals			
certificate of suitability			
<ul style="list-style-type: none"><li>• cULus approval</li></ul>	Yes		
design tested acc. to type of protection / EEx e	No		
overvoltage category	2		
degree of pollution	2		
combustibility class according to UL 94	V1		
standards, specifications, approvals / Environmental Product Declaration			
Environmental Product Declaration	Yes		
global warming potential [CO2 eq]			
<ul style="list-style-type: none"><li>• total</li><li>• during manufacturing</li><li>• during operation</li><li>• after end of life</li></ul>	282 kg 2.8 kg 278.9 kg 0.26 kg		
ambient conditions			
ambient temperature			
<ul style="list-style-type: none"><li>• during operation</li><li>• during storage</li></ul>	0 ... 60 °C -40 ... +70 °C		
mechanical data			
width × height × depth	130 mm × 76 mm × 60 mm		
mounting type	DIN rail 35 mm, DIN rail 15 mm		
mounting position	any		
height / with lowest-profile installation	60 mm		
net weight	0.36 kg		
insulation material	other		
color			
<ul style="list-style-type: none"><li>• of the enclosure</li><li>• of the light source</li></ul>	grey other		
product component / required / end cover plate	No		
further information / internet links			
internet link			
<ul style="list-style-type: none"><li>• to website: Industry Mall</li><li>• to web page: selection aid TIA Selection Tool</li><li>• to web page: system cabling</li><li>• to website: CAX-Download-Manager</li><li>• to website: Industry Online Support</li></ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://siemens.com/simatic-top-connect">https://siemens.com/simatic-top-connect</a> <a href="https://siemens.com/cax">https://siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>		
additional information			
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)		
marketing text	The TPRI relay connection module with relays for connecting 8 digital input signals (110VAC) and potential feed terminals (24VDC). For potential matching to 24VDC input signal. With screw terminals and LED for signalling, it forms the interface between the connection cables of the peripherals coming from the field and the SIMATIC S7. This is mounted on the DIN rail and, thanks to its functionality with screw terminals, is exactly adapted to the respective task. This connection module is part of the fully modular SIMATIC TOP connect connection for the fastest and safest system cabling. In addition to low wiring costs, error sources in cabling can be significantly reduced. Sensors and actuators from the peripherals are combined with the connection modules of SIMATIC TOP connect and connected to the SIMATIC S7-300/1500 via cable and front plug-in module.		
Classifications			
		Version	Classification
	eClass	14	27-25-01-12
	eClass	12	27-14-11-28
	eClass	9.1	27-14-11-28

eClass	9	27-14-11-28
eClass	8	27-14-11-28
eClass	7.1	27-14-11-28
eClass	6	27-14-11-28
ETIM	10	EC000900
ETIM	9	EC000900
ETIM	8	EC000900
ETIM	7	EC000900
UNSPSC	15	39-12-23-31

Approvals / Certificates

General Product Approval	EMV	Environment
--------------------------	-----	-------------

[Manufacturer Declaration](#)



last modified:

4/9/2025