

CONNECT. MOD. TP3 FUSE LED SCREW TERM.

Connection module TP3 with fuse per channel 8 channels and 2x10 terminals for Potential supply Type: Screw terminal with LED, VPE=1 unit 16 pole IDC connector f. cable



target system	SIMATIC S7-300 / 1500
suitability for use	Digital I/O modules
product type designation	Fully modular connection
product designation	Connection module
electrical data	
operating voltage	
• at DC / rated value	24 V
• rated value	24 V
• at DC / maximum	28.8 V
ampacity / per pin / maximum	1 A
continuous current / at DC / per signal cable / maximum	1 A
total current / maximum	4 A
display version	
• as status display of the inputs/outputs	LED yellow for "active high"
• for power supply / power LED	Yes; green for 24 V DC O.K.
product function / infeed function	Yes
product component	
• PE connection	No
• shield connection	No
• disconnecter	No
product feature / cross-connectable	No
connection method	
number of terminals	28; 8 x I/O; 10 x L+, 10 x M
number of channels	8
type of connecting terminal	Screw-type terminal
position / of the terminal	Top
number of terminal levels	1
design of terminal / terminal levels internally linked	No
type of electrical connection / for connecting cable	Plug-in connection
number of poles / at the 1st interface	16; IDC connector with installed strain relief for the connecting cable
number of the plug contacts / of the electrical connection	1
wire length / maximum	30 m; between front connector module and Connection module
type of connectable conductor cross-sections / solid	No
connectable conductor cross-section	
• for flexible conductor / with core end processing	0.5 ... 2.5 mm²; End sleeve according to DIN 46228/1
• stranded	0.5 ... 2.5 mm²
• finely stranded / with core end processing	0.5 ... 2.5 mm²
number of cables / per connection	2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule.
width of screwdriver blade	3.5 mm

tightening torque	0.4 ... 0.5 N·m
standards, specifications, approvals	
certificate of suitability	
• cULus approval	Yes
design tested acc. to type of protection / EEx e	No
overvoltage category	2
degree of pollution	2
combustibility class according to UL 94	V1

standards, specifications, approvals / Environmental Product Declaration

Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	37.8 kg
• during manufacturing	2 kg
• during operation	35.5 kg
• after end of life	0.19 kg

ambient conditions

ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C

mechanical data

width × height × depth	57 mm × 76 mm × 60 mm
mounting type	DIN rail 35 mm, DIN rail 15 mm
mounting position	any
height / with lowest-profile installation	60 mm
net weight	0.3 kg
insulation material	other
color	
• of the enclosure	grey
• of the light source	other
product component / required / end cover plate	No

further information / internet links

internet link	
• to website: Industry Mall	https://mall.industry.siemens.com
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to web page: system cabling	https://siemens.com/simatic-top-connect
• to website: CAX-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

additional information

other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
marketing text	The TP3f connection module for a 3-wire connection with 8 channels and potential connection with screw terminals, fuses for the signals and LED for signalling forms the interface between the connection cables of the peripherals and the SIMATIC S7 that are brought in from the field. This is mounted on the DIN rail and is exactly adapted to the respective task thanks to its functionality with screw terminals. This connection module is part of the fully modular SIMATIC TOP connect connection for the fastest and safest system cabling. In addition to low wiring costs, error sources in cabling can be significantly reduced. Sensors and actuators from the peripherals are combined with the connection modules of SIMATIC TOP connect and connected to the SIMATIC S7-300/1500 via cable and front plug-in module.

Classifications

	Version	Classification
eClass	14	27-25-01-12
eClass	12	27-14-11-28
eClass	9.1	27-14-11-28
eClass	9	27-14-11-28
eClass	8	27-14-11-28
eClass	7.1	27-14-11-28
eClass	6	27-14-11-28
ETIM	10	EC000900
ETIM	9	EC000900

ETIM	8	EC000900
ETIM	7	EC000900
UNSPSC	15	39-12-14-10

Approvals / Certificates

General Product Approval	EMV	Environment
--------------------------	-----	-------------

[Declaration of Con-
formity](#)
[Manufacturer Declara-
tion](#)



last modified:

4/9/2025