SIEMENS

Data sheet

6ES7972-0BA52-0XA0

product type designation product description



PROFIBUS connector

PROFIBUS bus connector, RS 485, Fast Connect, without programming port, 90° SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, Insulation displacement method FastConnect, without PG socket 15.8x 59x 35.6 mm (BxHxD)

suitability for use	for connecting PROFIBUS stations to the PROFIBUS bus cable
transfer rate	
transfer rate / with PROFIBUS DP	9.6 kbit/s 12 Mbit/s
interfaces	
number of electrical connections	
for PROFIBUS cables	2
 for network components or terminal equipment 	1
type of electrical connection	
• for PROFIBUS cables	Integrated insulation displacement terminals for 2-core PB FC installation cables
 for network components or terminal equipment 	9-pin sub D connector
type of electrical connection / FastConnect	Yes
mechanical data	
design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint
design, dimensions and weights	
type of cable outlet	90 degree cable outlet
width	15.8 mm
height	59 mm
depth	35.6 mm
net weight	36 g
ambient conditions	
ambient temperature	
 during operation 	-25 +60 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
protection class IP	IP20
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
product component	
 PG connection socket 	No
strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
 RoHS conformity 	Yes
 UL approval 	Yes

reference code

• according to IEC 81346-2

• according to IEC 81346-2:2019

XG XGA

further information / internet links

internet link

• to website: Selection guide for cables and connectors

• to web page: selection aid TIA Selection Tool

• to website: Industrial communication

• to web page: SiePortal

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

https://support.industry.siemens.com/cs/ww/en/view/109766358

https://www.siemens.com/tstcloud

https://www.siemens.com/simatic-net

https://sieportal.siemens.com

https://www.automation.siemens.com/bilddb

https://www.siemens.com/cax https://support.industry.siemens.com

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

Miscellaneous



Manufacturer Declaration





China RoHS

General Product Approval

EMV

For use in hazardous locations







FM



FM

For use in hazardous locations





Type Examination Certificate

CCC-Ex

last modified:

4/9/2025

