



-- spare part -- SCALANCE MUM853-1 5G router (EU), IP30, for wireless IP communication of Ethernet-based applications via public 3/4/5G mobile radio networks and private 5G networks, VPN, firewall, NAT, IPv6, connection to SINEMA RC via CLP, 4 SMA connections, 1x micro SIM slot, eSIM, 4x10/100/1000 Mbps RJ45 port, redundant DC 24 V, -30... +60 °C, CLP slot, 1x DI and 1x DO, observe national approvals: [siemens.com/mobile-approvals](https://www.siemens.com/mobile-approvals)

transfer rate	
transfer rate / for Industrial Ethernet	10, 100, 1000 Mbit/s
transfer rate	
<ul style="list-style-type: none"> with UMTS transmission / with downlink / maximum 	42 Mbit/s
<ul style="list-style-type: none"> with UMTS transmission / with uplink / maximum 	5.76 Mbit/s
<ul style="list-style-type: none"> for LTE transmission / with downlink / maximum 	1000 Mbit/s
<ul style="list-style-type: none"> for LTE transmission / with uplink / maximum 	200 Mbit/s
<ul style="list-style-type: none"> for 5G transmission / with downlink / maximum 	1000 Mbit/s
<ul style="list-style-type: none"> for 5G transmission / with uplink / maximum 	500 Mbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical/optical connections / for gigabit Ethernet / maximum	4
number of electrical connections	
<ul style="list-style-type: none"> for network components or terminal equipment 	4
number of electrical connections	
<ul style="list-style-type: none"> for external antenna(s) for power supply for redundant voltage supply 	4 1 1
type of electrical connection	
<ul style="list-style-type: none"> for internal network for external antenna(s) for power supply 	RJ45 port (10/100/1000 Mbps, TP, auto-crossover) SMA antenna socket (50 ohms) 5-pole terminal strip
memory	
number of slots / for Micro-SIM card	1
design of the removable storage / CLP	Yes
signal inputs/outputs	
number of digital inputs	1
number of digital outputs	1
type of electrical connection / at the digital inputs/outputs	terminal block
input voltage / at digital input / at DC	-30 ... +30 V
output voltage / at digital output / at DC / maximum	24 V; 0,5 A
operational current / of the signaling contacts / at DC / at 30 V / maximum	0.008 A
WAN connection	
type of wireless network / is supported	5G public networks, 5G private networks, LTE, UMTS
type of mobile wireless service / is supported	HSDPA, HSUPA, HSPA+
frequency band / is supported	
<ul style="list-style-type: none"> 5G Standalone (SA) 	n1, n3, n5, n7, n8, n12, n20, n28, n38, n40, n41, n48, n71, n77, n78, n79
<ul style="list-style-type: none"> 5G Non-Standalone (NSA) 	n1, n3, n5, n7, n8, n20, n28, n38, n40, n41, n48, n66, n77, n78, n79

- LTE

B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B32, B66, B71, B34, B38, B39, B40, B41, B42, B43, B46, B48
B1, B2, B3, B4, B5, B8

- UMTS

supply voltage, current consumption, power loss

consumed current	
<ul style="list-style-type: none"> • at DC / at 24 V 	0.55 A
<ul style="list-style-type: none"> • at DC / at 24 V / sleep mode / maximum 	0.013 A
supply voltage / 1 / rated value	24 V
<ul style="list-style-type: none"> • type of voltage 	redundant power supply, 24 V DC
<ul style="list-style-type: none"> • type of voltage / 1 / of the supply voltage 	DC
supply voltage / 2 / rated value	24 V
<ul style="list-style-type: none"> • type of voltage / 2 / of the supply voltage 	DC

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> • during operation 	-30 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C
relative humidity / at 25 °C / during operation / maximum	95 %
protection class IP	IP30

design, dimensions and weights

design	compact
depth	137 mm
height	157 mm
width	35 mm
net weight	680 g
fastening method	
<ul style="list-style-type: none"> • 35 mm DIN-rail mounting 	Yes
<ul style="list-style-type: none"> • S7-300 rail mounting 	Yes
<ul style="list-style-type: none"> • S7-1500 rail mounting 	Yes
<ul style="list-style-type: none"> • wall mounting 	Yes

product features, product functions, product components / general

product function	
<ul style="list-style-type: none"> • DynDNS client 	Yes
<ul style="list-style-type: none"> • no-ip.com client 	Yes

product functions / management, configuration, engineering

product function	
<ul style="list-style-type: none"> • CLI 	Yes
<ul style="list-style-type: none"> • web-based management 	Yes
<ul style="list-style-type: none"> • MIB support 	Yes
<ul style="list-style-type: none"> • TRAPs via email 	Yes
protocol / is supported	
<ul style="list-style-type: none"> • Telnet 	Yes
<ul style="list-style-type: none"> • HTTP 	Yes
<ul style="list-style-type: none"> • HTTPS 	Yes
type of configuration	Web-based management
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022

product functions / diagnostics

protocol / is supported	
<ul style="list-style-type: none"> • SNMP v1 	Yes
<ul style="list-style-type: none"> • SNMP v2 	Yes
<ul style="list-style-type: none"> • SNMP v2c 	Yes
<ul style="list-style-type: none"> • SNMP v3 	Yes
product function	
<ul style="list-style-type: none"> • statistics Packet Size 	No
<ul style="list-style-type: none"> • statistics packet type 	No
<ul style="list-style-type: none"> • error statistics 	No
<ul style="list-style-type: none"> • SysLog 	Yes
<ul style="list-style-type: none"> • packet filter log 	Yes

product functions / DHCP

product function	
<ul style="list-style-type: none"> • DHCP client 	Yes
<ul style="list-style-type: none"> • DHCP server - internal network 	Yes

product functions / routing	
router function	
• NAT (IP masquerading)	Yes
• port forwarding	Yes
• NAT traversal	Yes
• 1:1 NAT	Yes
• DNS cache	Yes
product functions / security	
suitability for operation / Virtual Private Network	Yes
firewall version	Statefull Inspection
product function	
• password protection	Yes
• packet filter	Yes
• broadcast/multicast/unicast limiter	No
product function	
• broadcast blocking	No
• with VPN connection	IPsec, OpenVPN (as Client)
number of possible connections / with VPN connection	20
type of authentication / with Virtual Private Network / PSK	Yes
protocol / is supported	
• IPsec tunnel and transport mode	Yes
key length	
• 1 / with IPsec AES / with Virtual Private Network	128 bit
• 2 / with IPsec AES / with Virtual Private Network	192 bit
• 3 / with IPsec AES / with Virtual Private Network	256 bit
• with IPsec 3DES / with Virtual Private Network	168 bit
type of Internet key exchange / with Virtual Private Network	
• main mode	Yes
• quick mode	Yes
type of packet authentication / with Virtual Private Network	MD5, SHA-1, SHA-256, SHA-384, SHA-512
IETF profile / with Virtual Private Network / X.509v3 certificate	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
standards, specifications, approvals	
standard	
• for EMC	ETSI EN 301 489-1, ETSI EN 301 489-19, ETSI EN 301 489-52, EN 55011, NAMUR NE21
• for emitted interference	CISPR 32, ETSI EN 55032 Class A / Class B, EN IEC 61000-6-3, EN IEC 61000-6-4
• for interference immunity	CISPR 35, EN 55035, EN IEC 61000-6-1, EN IEC 61000-6-2
certificate of suitability	
• EC Declaration of Conformity	Yes
• CE marking	Yes
reference code	
• according to IEC 81346-2:2019	KED
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
• total	390.86 kg
• during manufacturing	29.7 kg
• during operation	361 kg
• after end of life	0.16 kg
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Mobile radio national approval	https://www.siemens.com/mobile-approvals
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com/

- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://www.automation.siemens.com/bilddb>

<https://www.siemens.com/cax>

<https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval

Radio Equipment
Type Approval Certificate

Environment



[Type Examination Certificate](#)

[Miscellaneous](#)



last modified:

4/3/2025