

product type designation

product description

Cable for IO-Link, M12 / M12

Sensor cable (3-core)

SIMATIC RF IO-Link connecting cable, pre-assembled, between IO-Link master and reader, both ends M12 4-pole 3-core cable, PUR, length 5 m.



Figure similar

suitability for use

Plug-in cable for connecting an IO-Link device to an IO-Link master

cable designation

LiY-11Y 4xAWG 22/19

wire length

5 m

electrical data

number of electrical connections

2

type of electrical connection

M12 (male, 4 pin, straight) / M12 (female, 4 pin, straight)

loop resistance per length / maximum

108 mΩ/m

insulation resistance coefficient

20 GΩ·m

operating voltage

• maximum

30 V

mechanical data

number of electrical cores

3

design of the shield

unshielded

outer diameter

• of cable sheath

4.3 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.15 mm

material

• of the wire insulation

PVC

• of cable sheath

TPE-U Ether Isolation

color

• of the insulation of data wires

brown, white, blue, black

• of cable sheath

Black

bending radius

• with single bend / minimum permissible

34.4 mm

• with multiple bends / minimum permissible

64.5 mm

ambient conditions

ambient temperature

• during operation

-5 ... +80 °C

• during storage

-40 ... +80 °C

• during transport

-40 ... +80 °C

• during installation

-5 ... +80 °C

fire behavior

flame resistant according to AWM STYLE 21317 80°C 30V VW-1 for USA and AWM I/II A/B 80°C 30V FT-1 for Canada

product features, product functions, product components / general

product feature

• halogen-free

No

standards, specifications, approvals

reference code	
• according to IEC 81346-2 • according to IEC 81346-2:2019	WG WGB
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors • to web page: selection aid TIA Selection Tool • to web page: SiePortal • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates	
General Product Approval	EMV
   	China RoHS KC

last modified:

8/8/2024 